

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8582)

Set 1/4 sec. post, from which
A Fir 14" dia., bears N.60°W., 15 lks.
A Fir 12" dia., bears S.65°E., 12 lks.

George J. Wenderoth, Deputy - June 1957 (or 1953?) - C.S. File 45/154 and M 5-28

1" Iron pipe.
18" Fir N.60°W., 9.9 ft.
8" Cedar S.30°40'W., 26.2 ft.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17873-74)

The 1/4 sec. cor., perpetuated and recorded by Wenderoth in 1953, monumented with an iron pipe, 1" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree:

A Fir snag, 18" dia., bears S.60°E., 12 lks. dist., with chopped open blaze, no marks visible. (Rec. S.65°E.) and a bearing tree mkd. by Wenderoth:

A Fir 21" dia., bears N.57 1/2°W., 15 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 21 ins. in the ground, directly over iron pipe, with brass cap marked

T 32 S R 5 W

1/4

S 23 | S 24

1983

from which a new bearing tree

A Fir 6" dia., bears N.69 1/2°E., 38 lks. dist., mkd. 1/4 S24 BT.

Fd. OK by Nygren, Aug. 1998 - M130-34

Fd. BC & 2 BTs, D.Edwards 4/2008 M155-51