

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8557-58)

-----  
The cor. of secs. 13, 14, 23 and 24, from which  
A Laurel 10" dia., bears \*~~N.30°E.~~, 11 lks. \*N.39°E. per  
A Vine Maple 3" dia., bears S.25°E., 50 lks. research  
A Dogwood 8" dia., bears S.63°W., 30 lks. 4/15/2025  
A Vine Maple 3" dia., bears N.67½°W., 27 lks.

George J. Wenderoth - June 1957 (or 1953?) - C.S. File 45/154 and M 5-28

-----  
1/2" Iron pipe.  
16" Cedar S.69°39'W., 26.0 ft.  
12" Fir S.58°30'E., 57.4 ft.  
12" Cedar N.35°W., 31.1 ft.  
7" Cedar N.22°30'E., 28.8 ft.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17875)

-----  
The Sec. cor., perpetuated and recorded by Wenderoth in 1953, from original evidence no longer in existence. Mr. Donald W. Brady, a resident of the area for many years, furnished a signed statement, attached to and made a portion of these field notes, attesting to the corner position. The corner is monumented with an iron pipe, ½" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Wenderoth:  
A Cedar 15" dia., bears N.20°E., 44 lks. dist., with healed blaze.  
A Fir 22" dia., bears S.60½°E., 88 lks. dist., with healed blaze.  
A Cedar 19" dia., bears S.67°W., 40½ lks. dist., with healed blaze.  
A Cedar 21" dia., bears N.37½°W., 47 lks. dist., with healed blaze.  
and a bearing tree mkd. by person(s) unknown:  
The East fork of a twin Fir 24" dia., bears S.31½°W., 22 lks. dist., with healed blaze, at breast height.

At the corner point  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, directly over iron pipe, with brass cap marked

T 32 S R 5 W  
S 14 | S 13  
S 23 | S 24  
1983

(no new BTs listed by BLM)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Found OK by Nygren, Aug. 1998 - M130-34