

PRIMARY CORNER DESCRIPTION Sec Cor for 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8558-59)

Set post, cor. to secs. 11, 12, 13 and 14 in edge of prairie S.40°E. and N.50°W., from which
A B.Oak 11" dia., bears N.66°E., 114 lks.
A W.Oak 12" dia., bears N.64½°W., 215 lks.
A W.Oak 4" dia., bears S.69½°W., 119 lks.
A W.Oak 6" dia., bears S.26°E., 203 lks.

Frank Cain, Deputy - Recorded by F.C. Frear, County Surveyor - Oct. 14, 1920 - Field Book 107 Pg. 37 ("old" corner book, pg. 171)

Iron wagon axle, from which
A W.Oak 14" bears N.41°E., 39 lks. CS BT.
A W.oak 12" bears N.35 3/4°W., 13 lks. CS BT.
A B.Oak 15" bears S.41¼°E., 31 lks. CS BT.
A W.Oak 10" bears S.37 3/4°W., 77 lks. CS BT.

George Wenderoth - 1951 - C.S. File 45/228 and M 3-9

Wagon axle.
11" B.Oak N.66°E., 75.2 ft.
12" W.Oak N.64°30'W., 141.9 ft.
4" W.Oak S.69°30'W., 78.4 ft.
8" W.Oak S.26°E., 134.0 ft.

George Wenderoth - Oct. 1954 - C.S. File 46/52 and M 3-9

Wagon axle lying on ground. Drive a 3/4" Iron pipe for corner. All BTs in good shape:
14" B.Oak N.66°E., 75.2 ft.
16" W.Oak N.64°30'W., 78.4 ft.
8" W.Oak S.69°30'W., 78.4 ft.
12" W.Oak S.26°E., 134 ft.

Douglas Co. Surveyors Office - James Byron - For: Douglas Co. Road Dept. - Dec. 1956 - C.S. File 48/36 (Rd. #36 envelope)

Found - 3/4" Iron pipe at fence corner and SW BT as renewed by Wenderoth.
Blazed and scribed:
10" R.Fir "S12 CS BT", N.65°E., 15.0 ft.
8" R.Fir "S13 CS BT", S.51°E., 57.4 ft.
20" W.Oak "S11 CS BT", N.29°W., 29.0 ft. "T32S R5W".

PRIMARY CORNER DESCRIPTION Sec Cor for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John Powell, Frank Jones, Joe Brady, crew - Aug. 9, 1967 - C.S. File 53/52-21

Found - 3/4" Iron pipe at corner marked.
8" now 10" R.Fir S.51°E., 54.0 ft., shows good face.
10" now 12" D.Fir N.65°E., 15.0 ft., shows good face.
20" now 24" W.Oak N.29°W., 29.0 ft. shows good face.
New BT - 8" W.Pine S.88°W., 28.8 ft. mkd. "1/4 S14 CS BT"
This corner lies at a NE fence corner in an Oak grove.

Survey by Bruce Shaner, LS #430 - June 9, 1988 - C.S. File 63/85-11

Found - 3/4" Iron pipe.
16" Fir, face overgrown, bears S.51°E., 57.4 ft.
(Powell's record, 54.0 ft. but Byron, 1956 shows 57.4 ft.)
18" D.Fir, face overgrown, bears N.65°E., 15.0 ft.
14" W.Oak, face rotted out, bears N.35 3/4°W., 8.6 ft. (as per record by Frear in 1920)
Set 2 1/2" brass cap mounted on a 2" x 30" galv. iron pipe, 24" in the ground, in place of 3/4" I.pipe. Cap mkd: "T32S R5W W.M. S11|S12 1988 RLS 430"
S14|S13
Reset 3/4" iron pipe alongside brass cap.

Fd. As per record by M. Heimburger 9/2020 - M178-15A-C