

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8560)

-----  
Set ¼ sec. post, on SW slope, from which  
A W.Oak 18" dia., bears S.85°W., 29 lks.  
A B.Oak 16" dia., bears S.12°E., 106 lks.

W.F. Briggs, Co. Surveyor - For: G.B. Johns & Sons - July 31, 1900 - Vol. 2 Page 99

-----  
Set regulation post at ¼ cor., from which Orig. bearing trees standing to wit:  
W.Oak 18" dia., bears S.85°W., 29 lks.  
B.Oak 16" dia., bears S.12°E., 106 lks.

Frank Cain, Deputy - Recorded by F.C. Frear, Co. Surveyor - Oct. 14, 1920 - Field Book 107 Page 38 (and "old" corner book, Pg. 171)

-----  
Stone 6" x 8" x 14" marked X, from which  
A W.Oak 42" bears S.85°W., 29 lks. Remarked.  
A Pine 18" dia., bears S.78 ¾°E., 74 lks.

G.J. Wenderoth - August 1952 - C.S. File 45/98 and M 3-9

-----  
Set Axle shaft.  
50" W.Oak S.85°W., 19.1 ft.  
12" B.Oak S.34°50'W., 60.9 ft.  
12" B.Oak N.85°30'E., 68.4 ft.

Cor. Fd. OK, DCSO, John Powell, Aug.17, 1967- C.S. 53/52-12  
Fd. OK, Hull, Jan. 1989, M 107-39

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21695-6)

-----  
The ¼ sec. cor. of secs. 11 and 12, perpetuated by the Douglas County Surveyor's Office in 1900, 1920, and further perpetuated by Douglas County Surveyor's Office in 1952, monumented with an axle, 1" dia., firmly set, flush with the ground, from which an original bearing tree:

A hollow white oak, 41" dia., bears S.85°W., 19.1 ft., with a partially healed blaze.  
and remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1952

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A broken off black oak snag, 18" dia., bears N.84°E., 68.5 ft., with a healed double blaze.

An oak, 10" dia., bears S.33½°W., 60.8 ft., with a healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., flush with the surface of the ground, directly over axle, with brass cap mkd.

T 32 S R 5 W

¼

S 11 | S 12

2006

from which a new bearing tree

A white oak, 18" dia., bears N.75½°E., 60.0 ft., mkd. ¼ S12 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd. BC per rec. 4/2019 by M Heimburger - M175-43

Fd. As per record by M. Heimburger 9/2020 - M178-15A-C