

PRIMARY CORNER DESCRIPTION Sec Cor for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8560)

Set post, cor. to secs. 1, 2, 11 and 12, from which
A Fir 3" dia., bears N.61°W., 7 lks.
A Fir 16" dia., bears N.77°E., 10 lks.
A Fir 9" dia., bears S.19°E., 12 lks.
A Fir 18" dia., bears S.62°W., 47 lks.

George J. Wenderoth - Wit: F. Dean - August 1951 or 1952 - C.S. File 41/18; C.S. File 45/98 and M 7-61 and M 3-9

Found - Yew stake and 15" Fir N.61°W., 4.6 ft.
Drive 3/4" Iron pipe.
Scribe - 12" Fir N.34°15'W., 90.6 ft.
20" Fir S.60°15'W., 48.9 ft.
18" Fir N.86°07'E., 49.2 ft.
16" Fir S.75°22'E., 44.5 ft.

Cadastral survey by Hans W. Thielsen under Group #320 Surveyed, Oct./Nov. 1966 (DCSO records Vol. 28 Page(s) 11793-94)

The Sec. cor., perpetuated by an iron pipe 1" dia., 8" above ground, set by the County Surveyor in 1951.
from which an origina bearing tree
A Fir 20" dia., bears N.61°W., 7 lks. dist., marked with burned face of blaze.
and bearing trees marked by the County Surveyor:
A sawed Fir stump 18" dia., bears N.68°E., 76 lks. dist. with marks BT uncovered.
A sawed Fir stump 16" dia., bears S.76°E., 68 lks. dist. marked S12 CS BT.
A Fir 20" dia., bears S.60°W., 75 lks. dist., marked S11 CS BT.
A Fir snag 12" dia., bears N.35°W., 138 lks. dist., marked S2 CS BT.

At the corner point
Set an iron post, 36 ins. long, 2 ins. dia., 30 ins. in the ground, with brass cap marked

T 32	S R 5 W
S 2	S 1
S 11	S 12

1955

from which new bearing trees:
A W.Fir 13" dia., bears N.32½°E., 114 lks. dist., marked T32S R5W S1 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Red Fir 10" dia., bears S.42°E., 109 lks. dist., marked T32S R5W S12 BT.
A Red Fir 18" dia., bears S.33°W., 90 lks. dist., marked T32S R5W S11 BT.
A Red Fir 9" dia., bears N.61¼°W., 104 lks. dist. marked T32S R5W S1 BT.
Reset pipe alongside the iron post.

Fd. OK, per Max Hull, Jan. 1989, M 107-39

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2707, surveyed April/May 2013 - (DCSO records, Vol. 58 Page(s) 23130-1)

The cor. of secs. 1, 2, 11, & 12, monumented with an iron post, 2" dia., firmly set, projecting 8 ins. above the ground, with brass cap (properly) mkd. from which the remains of a BT mkd. by the Douglas County Surveyor's Office, in 1951
A sawed fir stump, 22" dia., bears S.60°W., 49.5 ft., with no scribe marks visible on partially healed blaze. and a BT mkd. by Thielsen in 1955
A fir snag, 20" dia., bears N.32½°E., 73.9 ft., with illegible scribe marks visible on partially healed blaze. (Record, 75.2 ft.)
and new bearing trees
A fir, 13" dia., bears N.37¼°E., 65.7 ft., mkd. T32S R5W S1 BT.
A cedar, 8" dia., bears S.76½°E., 13.0 ft., mkd. X at breast height and BT at base.
A cedar, 9" dia., bears S.57¼°W., 46.7 ft., mkd. T32S R5W S11 BT.
A pine, 13" dia., bears N.26°W., 62.9 ft., mkd. T32S R5W S2 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
NAD 1983 (2011)
Latitude: 42°48'41.94"N. Longitude: 123° 14' 53.09" W.

Fd. As per record by M. Heimburger 9/2020 - M178-15A-C