

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 640140

PRIMARY CORNER DESCRIPTION Center ¼ Cor. for Sec. 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Lloyd D. Smith - For: Ore. State Bd. of Forestry -
May 14, 1982 - M 92-34

Set OSBF 1½" x 36" galv. I.P. with 3" bronze cap, 30" in
ground.

New BTs -35" Sugar Pine bears N.29°E., 56.7 ft. YMLP

29" Fir bears N.67°W., 42.3 ft.

4" x 4" x 72" white painted Cedar post bears
S.48°E., 1.7 ft.

BT distances measured to face of BTs.

James McIntosh - For: State of Oregon, Dept. of Forestry -
April 2012 - M 163-54

Found - OSBF P/C (1½"x36" galvanized iron pipe with 3"
bronze cap) 1982, in place.

35" Sugar Pine bears N.29°E., 56.7 ft. YMLP (Now 41"
in place, face closed)

29" Fir bears N.67°W., 42.3 ft. (now 33" in place,
face closed, added BT tag)

White painted cedar post S.48°E., 1.70' (now rotted
and fallen over)

New - WP (Orange carsonite marker CBM-250 labeled Witness
post) S.40°E., 2.45' to base.

WP S.46°W., 3.00' to base.

YMLP (Yellow metal location poster) on 8" fir
S.80°E., 325.0' on west side of spur road.