

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8591)

Set a Cedar post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor., marked 1/4 S25 on N., and 36 on S. face, from which

A Fir 18" dia., bears S.46°W., 57 lks. mkd. 1/4 S36 BT.

A Fir 30" dia., bears N.46°E., 22 lks. mkd. 1/4 S25 BT.

This post stands in a little run, 1 lks. wide, course N.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - June 1964 - C.S. File 53/52-64

Found - 30" Fir N.46°E., 14.5 ft., uprooted, down and dead.
Cut open and found good scribing.

No trace found of SW tree.

Position for 1/4 corner falls in creek. Set witness corner 10 ft. West of 1/4 corner.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 5 W

W.C. 10 ft. E. to 1/4

S 25

S 36

1964

New BTs -42" D.Fir S.60°W., 33.8 ft. mkd. "WC 1/4 S36 CS BT", bark scribed.

36" D.Fir N.33°E., 70.9 ft. mkd. "WC 1/4 S25 CS BT" in wood.

Fd. OK, by L.D. Smith, May 14, 1982, M 92-34