

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8557)

Set qr. sec. post, from which
A Laurel 12" dia., bears N.61°W., 11 lks.
A Fir 9" dia., bears S.10°W., 3 lks.

Survey by Richard L. Templin, Jr. - For: Sierra Land Co. - April 30, 1956 - C.S. File 42/133

Corner not found. Set by single proportion.
Set 1" Channel bar, and scribed:
14" Fir S.43°30'E., 39.2 ft. mkd. ¼ S24 RE 3024 BT.
48" Fir N.24°05'E., 65.4 ft. mkd. ¼ S13 RE 3024 BT.

Administrative survey by BLM, Medford District - April 1979 -M 78-43

Set 5/8" x 24" rebar.
BTs - 12" D.Fir bears N.03¼°E., 30.8 ft.
13" D.Fir bears S.14¼°E., 31.0 ft.

Fd. OK by Nygren, Aug. 1998 - M130-34