

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8561)

Set ¼ sec. post, from which
A B.Oak 4" dia., bears N.25°W., 5 lks.
A Laurel 10" dia., bears S.57°E., (omitted)

George J. Wenderoth - Wit: Paul Newman - August 1951 - C.S. File 41/18 and M 3-9

Set halfway between section corners, 3/4" I.Pipe.
24" Madrona N.42°10'E., 52.9 ft.
24" Madrona S.75°40'E., 19.2 ft.

Fd. OK, per Max Hull, Jan. 1989, M 107-39

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2707, surveyed April/May 2013 - (DCSO records, Vol. 58 Page(s) 23129-30)

The ¼ sec. cor. of secs. 1 and 12, reestablished by Wenderoth, in 1951, by proportionate measurement. There is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron pipe, 3/4" dia., firmly set, projecting 2" above the ground.

from which the remains of a bearing tree mkd. by Wenderoth
A roothole with rotted madrone alongside, size indeterminate, bears N.41°E., 54.0 ft., no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, directly over the iron pipe, with brass cap mkd.

T 32 S R 5 W

¼ $\frac{S \ 1}{S \ 12}$
2013

and new bearing trees

A fir, 8" dia., bears S.7°E., 8.1 ft., mkd. ¼ S12 BT.

A pine, 10" dia., bears N.44¾°W., 24.1 ft., mkd. ¼ S1 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.