

PRIMARY CORNER DESCRIPTION Closing Cor Secs 30 & 31 only, T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, Under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8474-75)

I Set a Live Oak post, 3 ft. long, 4" sq., 24" in the ground, for a closing corner of secs. 30 and 31, marked: C.C. T32S R4W on E.; S30 on N.; and S31 on S. faces, with 1 groove on S. and 5 grooves on N. faces; from which

A Madrona 10" dia., bears S.62°E., 37 lks. dist., marked T32S R4W S31 BT.

A Fir 12" dia., bears N.48°E., 20 lks. dist., marked T32S R4W S30 BT.

This corner is on top of spur, sloping S.

Milo E. Godfrey, Deputy - Wit: Mike Stone - June 1964 - C.S. File 53/52-63

Found - Madrone, now 13" dia., S.62°E., 24.4 ft. Partial scribing visible on partly rotted face.

Rotten Fir stump N.48°E., 13.2 ft. Found good reverse scribing "BT" on decayed overgrowth of old face.

Set Brass cap at cor. mkd: County Surveyors Office

	T	32	S				
R	5	W		S 30	R	4	W
				S 31			
				CC			
				1964			

New BTs -14" Madrone N.8°E., 16.5 ft. mkd. T32S R4W S30 CC CS BT.

4" D.Fir S.73°E., 13.5 ft. mkd. CC S31 CS BT.

19" Live Oak S.9°W., 20.0 ft. mkd. CC S30 S31 CS BT

Corner lies directly on top of ridge.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #977 Surveyed, May/June 1979 - (DCSO records Vol. 43 Page(s) 16770)

True point for the closing cor. of secs. 30 and 31. Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 32 S

R	5	W		R	4	W		
				S	25		S 30	CC
							S 31	
							1979	

from which

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 700211

PRIMARY CORNER DESCRIPTION C.C. for Secs. 30 and 31 only, T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 12" dia., bears N.13½°E., 63½ lks. dist., mkd. T32S R4W S30 CC BT.

A Fir 6" dia., bears S.24½°E., 6¼ lks. dist., mkd. S R4W S31 CC.

From the same point, the original closing cor. of secs. 30 and 31, bears N.89°47'W., 0.18 chs. dist., perpetuated and recorded by Godfrey in 1964, monumented with a galv. iron pipe, 1" dia., firmly set, projecting 13" above ground, with marked brass cap.

from which the remains of the original bearing trees

A burned and rotted Fir stump 12" dia., bears N.48°E., 20 lks. dist., with scribe marks S R4W visible on portion of burned blaze.

A Madrone 13" dia., bears S.62°E., 37 lks. dist., with decayed blaze.

and bearing trees mkd. by Godfrey:

A Madrone 13" dia., bears N.7¼°E., 25 lks. dist., with scribe marks T32S R4W S30 CC BT visible on partially healed blaze.

A Fir 6" dia., bears S.73°E., 20½ lks. dist., with healed double blaze.

A Live Oak 18" dia., bears S.8°W., 30¼ lks. dist., with illegible scribe marks visible on partially healed double blaze.