

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18 of T32-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 20 Pg 8453)

Set ¼ sec. post, from which
A Fir 18" dia., bears N.21°W., 123 lks.
A Fir 18" dia., bears S.56°E., 81 lks.

Douglas Co. Surveyors Office - George Wenderoth, Deputy -
Wit: Clifford Worley - Oct. 1946 - C.S. File 39/158

Set halfway between corners.
Drive 1" bar for corner.
Scribed -An 18" Fir S.16°00'E., 25.0 ft.
A 16" Fir N.76°15'W., 29.7 ft.

Douglas Co. Surveyors Office - John Powell and crew - May 13,
1970 - C.S. File 54/114-23

Found - 1" Iron rod at ¼ corner.
Scribed post, "¼ S 18 - 13".
16" Fir now stump, N.76°W., 29.7 ft. scribe visible.
No trace of SE BT, skid road.
New BT - 13" D.Fir S.48°W., 48.3 ft. mkd. ¼ S13 CS BT.
No other trees available.
Location tag on Fir stump near old logging road bears West, 80 ft.

Survey by James Artman L.S. #2268 - For: Medford Corporation
March 16, 1990 - M 109-66 and C.S. File 63/101

Found - 18" D.Fir bears N.51°W., 43.0 ft. healed face.
16" D.Fir stump bears N.69°W., 28.0 ft. scribes
visible.
Set 5/8" x 30" Iron rod with cap mkd: "Artman RLS 2268".
New BTs -7" D.Fir bears N.28°E., 10.5 ft. scribed ¼ S18 BT.
7" D.Fir bears N.74°W., 8.7 ft. scribed ¼ S13 BT.
9" D.Fir bears S.89°E., 8.6 ft. scribed ¼ S18 BT.
1" Iron pipe bears N.13°41'07"E., 5.86 ft.

Fd. 5/8" I.R. OK, Raymond Brown, July 1993, M 117-58
Found OK by R. Brown, Nov. 2002 - 2002-0059

Kristian DeGroot - For: Silver Butte Timber Co. - 10/2010 -
M157-32

LAT: 42°47'23.100860" N. LONG: 123°13'42.458646" W.
Found a 1¼" round head x ¾" round iron bar, by Wenderoth per
C.S. 39/159, firmly set, projecting 6" above the ground.
continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18 of T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From which bearing trees by Wenderoth in 1946:
A 16" rotted D.Fir stump bears N.78°15'W., 29.9 ft.
And bearing trees by DCSO - John Powell in 1970:
A 27" D.Fir bears S.48°45'W., 48.5 ft. with healed blaze
And BTs by Artman per M106-66 with new ties:
A 5" down madrone bears N.8°30'E., 5.3 ft to roothole
A 10" D.Fir bears S.46°E., 6.2 ft. with healed blaze faced
to Artman's corner
A 9" D.Fir bears S.81°15'W., 12.1 ft. with healed blaze
faced to Artman's corner and a monument per M109-66:
A 5/8" IR bears S.40°53'14"E., 5.91 ft This corner was
errantly set by improper boundary control procedures,
and therefore rejected. I drive rod 3" below ground.