

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. cor. (NE Cor. Sec. 1)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and Geo. Hyde under Contract #39 dated Jan. 4, 1854 (DCSO records Vol. 18 Page(s) 7781)

-----  
Set post, cor. of Tps. 31 and 32 S., Rs. 4 and 5 W., from which

- A Fir 5" dia., bears N.15°W., 22 lks.
- A Fir 18" dia., bears N.62°E., 33 lks.
- A Fir 10" dia., bears S.55°E., 104 lks.
- A Fir 3" dia., bears S.75°W., 47 lks.

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 18 Page 7782)

-----  
Found all witness trees destroyed except one. Stake rotted off at the ground, stub remaining in place. Witness tree:

- A Fir 24" dia., bears N.62°E., 33 lks. dist.

GL0 survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7853)

-----  
The post cor. to tps. 31 and 32 S., Rs., 4 and 5 W is gone. I find 1 witness tree.

At cor. point

Set a stone, 16x10x10 ins., 12" in the ground, for cor. to tps. 31 and 32 S., Rs., 4 and 5 W marked with 6 notches on each edge; from which

- A Fir 18" dia., (24" now) bears N.62°E., 33 lks. dist., marked T31S R4W S31 BT.

The other witness trees have been destroyed by fire.

I mark 3 new trees as follows:

- A Fir 36" dia. bears S.76°E., 40 lks marked T32S R4W S6 BT
- A Fir 10" dia. bears S.66°W., 57 lks marked T32S R5W S1 BT
- A Fir 10" dia bears N.13½°W. 82 lks marked T31S R5W S36 BT

Survey by John H. Markham, Jr. - Wit: Martin Perry - May 14, 1951 - C.S. File 40/312-2

-----  
Determined by O.B.T.

- A Fir 54" dia., bears S.73°E., 26.0 ft. (O.B.T.)
- A Fir stump, logged, 24" dia., bears N.67°E., 21.0 ft. (O.B.T.) I marked on top of stump, S31 BT.
- A Fir 20" dia., bears S.63°W., 38.0 ft. (O.B.T.)

At corner point, set 3/4" x 24" Iron pipe and found original stone, from which

- A Fir 7" dia., bears N.82°E., 10.0 ft. mkd. S31 BT.

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. Cor. (NE Cor. Sec. 1)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Richard Templin Jr. - Sept. 1958 - C.S. File 42/389

-----  
Found - 3/4" iron pipe (unmarked)  
24" Fir S.62 3/4°W., 39.5 ft. blaze healed.  
50" Fir stump S.74½°E., 25.5 ft. scribing visible.  
40" Fir stump N.65°E., 20.0 ft. blaze healed.  
16" Fir stump N.16°W., 54.0 ft. blaze healed.  
10" Fir N.79 3/4°E., 9.8 ft. scribing visible.  
Scribed: 6" Cedar N.27°W., 16.6 ft. mkd. S36 RE 3024 BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCS0 records Vol. 38 Page(s) 15641)

-----  
The Tsp. corner, perpetuated and recorded by Templin in 1958, monumented with an iron pipe 1" dia., firmly set, protruding 6" above ground, alongside of which is a basalt stone, 16 x 10 x 10 ins., loosely set, 2" in the ground, mkd. with 6 notches on each edge, from which the remains of the original bearing trees:

A Fir stump 39" dia., bears N.62°E., 33 lks. dist., no marks visible.  
and the remains of bearing trees mkd. by Bushey:  
A Fir stump 65" dia., bears S.76°E., 40 lks. dist., with scribe mark S visible on opened blaze.  
A Fir 35" dia., bears S.62°W., 60 lks. dist., with healed blaze. (Record, S.66°W., 57 lks.)  
and a bearing tree mkd. by Templin:  
A Cedar 8" dia., bears N.25½°W., 25 lks. dist., with healed blaze.

At the corner point  
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T 31 S  
R 5 W R 4 W  
S 36 | S 31  
S 1 | S 6  
T 32 S  
1973

from which new bearing trees  
A Fir 14" dia., bears N.63°E., 47 lks. dist., marked T31S R4W S31 BT.  
A Fir 12" dia., bears S.50°E., 53 lks. dist., marked T32S R4W S6 BT.  
Deposit iron pipe and stone alongside iron post.

Fd. Ok - R. Templin - July 1994 - 1995-0115 A&B

cont.

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. cor. (NE Cor. Sec. 1)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

The cor. of Tps. 31 & 32 S., Rs. 4 & 5 W., monumented with an iron post, 2½" dia., firmly set, projecting 2" above the ground with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed fir stump, badly decayed, 38" dia., bears N.62°E., 21.8 ft., no marks visible.

and the remains of bearing trees mkd. by Bushey in 1894

A sawed fir stump, 63" dia., bears S.74°E., 28.0 ft., with illegible scribe marks visible on open blaze. (Record, S.76°E., 26.4 ft.)

A fir, 42" dia., bears S.62°W., 38.9 ft., with a healed blaze. (Record, 39.6 ft.)

and a bearing tree mkd. by Templin Jr., RPE No. 3024, in 1958

A cedar, 16" dia., bears N.27°W., 16.5 ft., with a healed blaze. (Record, N. 25½°W.)

and the remains of BTs mkd. by Berry and Akin Jr. in 1972-73

A fir, 25" dia., bears N.63°E., 31.0 ft., with a healed blaze.

A sawed fir stump, 18" dia., bears S.50°E., 35.0 ft., with a healed blaze.

and a new bearing tree

A fir, 8" dia., bears S.56¾°E., 22.9 ft., mkd. X at breast height, and BT at base.

NAD 1983 (2011)

Latitude: 42°49'33.58" N. Longitude: 123°13'42.07"W.

Ron Quimby - Crew: N. Fromdahl & R. Olson - 9/2015 - C.S.  
File 65/89-41

-----  
Found - 3" BLM brass cap (properly mkd)  
38" fir stump N.62°E., 21.8 ft. - badly decayed  
25" fir N.63°E., 31.0 ft. - Good scar.  
63" fir stump S.74°E., 28.0 ft. - Vis. scar.  
18" fir stump S.50°E., 22.9 ft. - Good scar.  
42" fir S.62°W., 38.9 ft. - Good scar.  
17" cedar N.27°W., 16.5 ft. - Good scar.

Note - Corner is on a NE slope approx. 500' west of road.  
N 42°49'33.58" W 123°13'42.07"  
Compass decl. 15½°E.