

PRIMARY CORNER DESCRIPTION NNE Cor. Redfield DLC #38 (Sec. 35)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856

Set a post, from which
A W.Oak 18" dia., bears S.80°W., 505 lks.

F.C. Frear - N. Richardson - August 1942 (No record source found - see "old" corner book, Page 172)

Renewed from old BT which is in good shape.
Set Iron pipe 2" x 48" and remarked original tree with "BT"

Ben B. Irving, County Surveyor - James Byron and Ray Irving, crew - Decs. 21-24, 1953 - C.S. File 45/249 and M 9-19

Found - 2" Iron pipe.
Blazed O.B.T., 36" W.Oak S.82°39'W., 332.6 ft. (Rec. S.80°W.)
Blazed and scribed two new trees:
12" W.Oak N.88°04'W., 48.7 ft. mkd. NE Cl 38 CS BT.
12" W.Oak N.12°06'W., 92.6 ft. mkd. NE Cl 38 CS BT.

Fd. OK, March 1973, RM 2-43
Fd. Ok, Aug. 1975 by Ron Brandt, M58-8

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 4-7-2005 - C.S. File 67/10-20

Found - 2" inside dia., iron pipe, leans WSW approx. 4" projects 12" above ground.
12" now 15" dia., W.Oak, healed blaze visible bears S.86°W., 48.7 ft. (rec. N.88°04'W., 48.7 ft. 1953)
12" now 19" dia., W.Oak, healed blazes visible bears N.13¾°W., 92.6 ft. (Rec. N.12°06'W. 92.6 ft. 1953)
18" now 36" W.Oak, healed blaze visible bears S.80°W., 333.3 ft. (agrees w/1856 rec.) OBT
New - Brass disc stamped "C108 1973 DOUGLAS COUNTY SURVEYOR" set in concrete filled bell tile bears S.81½°W., 307.8 ft.
Note - Iron pipe lies just inside corner of fences running south & west over nearly level ground.
Comp. decl. 16¾°E.

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 038010

PRIMARY CORNER DESCRIPTION NNE Cor. Redfield DLC #38 (Sec. 35)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21441)

The Northern most NE exterior cor. of DLC No. 38, reportedly perpetuated by Frear and Richardson in 1942, further perpetuated by the Douglas County Surveyor's Office in 1953 and 2005, and utilized by various Oregon Professional Surveyors, monumented with an iron pipe, 2" dia., firmly set, projecting 12" above the ground, from which the original bearing tree

A W.Oak, 36" dia., bears S.80°W., 333.3 ft., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1953

A W.Oak, 15" dia., bears S.84½°W., 48.8 ft., with a healed blaze.

A W.Oak, 19" dia., bears N.15°W., 92.7 ft. with a healed blaze.

At the corner point

Set an iron rod, 63" long, 5/8" dia., 51" in the ground, directly inside the center of the iron pipe, with an aluminum cap mkd.

