

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Redfield DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856

Set a Post, from which
A B.Oak 14" dia., bears S.41°30'E., 75 lks.

Survey by Max H. Hull - For: C.A. Root - April 1973 - C.S. File 55/288 and RM 2-43

Found - 30" B.Oak with scribe S.41°31'E., 49.5 ft.
Set 5/8" Iron Rod.
Scribed -6" Cedar N.31°E., 7.92 ft.
12" Fir N.79°W., 12.95 ft.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21443)


The NW corner of DLC No. 38, perpetuated from original evidence no longer in existence, by Hull, in 1973, monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above the ground, with a plastic yellow cap mkd. HULL RS 901, from which bearing trees mkd. by Hull

A red cedar, 7" dia., bears N.27¾°E., 7.9 ft., with fragmentary scribe marks visible on partially healed blaze.

A D.Fir, 14" dia., bears S.74¼°W., 12.4 ft., with a healed upper and lower blazes.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, directly over the iron rod, in a collar of stone, with brass cap mkd.



Deposit a magnet in a white plastic case at the base of the stainless steel post.