

PRIMARY CORNER DESCRIPTION SE Cor. Redfield DLC #38 (Sec. 35)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856

Set a post, from which
A Fir 30" dia., bears N.15°W., 135 lks. dist.

Ben B. Irving, County Surveyor - James Byron, Ray Irving, crew - Dec. 21-24, 1953 - C.S. File 45/249 and M 9-19

Set 1" Iron pipe on side of fill of relocated Pacific Hwy. for corner, mkd. S.E. corner D.L.C. 38.
Found - 5/8" iron rod on R/W P.O.C. 452+64.36, N.5°03'W., 337.3 ft.
5/8" iron rod on R/W P.O.C. 455+97.75, N.89°14'30"W., 263.0 ft.
3" x 3" squared post, N.89°14'W., 59.4 ft.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 4/20/2005 - C.S. File 67/10-21

Found - 1" pipe called for in 1953 renewal NOT FOUND position falls in wide median of Interstate 5 near Glendale interchange.

5/8" I.Rod w/4x4 post alongside. Post is marked "SHRW POC 455+97.75. Iron rod is smooth & projects above ground 4"

The other R/W monument (POC 452+64.36) called out in the 1953 renewal was searched for & not fd. Position falls in large fill bank for I-5 Southbound lanes.

New - The fd. 5/8" IR will now become the reference monument to SE cor. DLC 38. DLC Corner bears

S.89°14'30"E., 263.0 ft. from fd. 5/8" IR.

9" Madrone, double blazed & scribed "RM CS BT", bears S.1½°E., 11.2 ft.

8" dia., Grand Fir, double blazed & scribed "RM CS BT" bears S.65°E., 22.4 ft.

23" dia., D.Fir, double blazed & scribed "RM CS BT" bears N.81°E., 9.6 ft.

11" dia., Madrone, double blazed & scribed "RM CS BT" bears S.83¾°W., 28.5 ft.

Note - Corner lies on North facing slope, on West side of Glendale Interchange & approx. 150 ft. West of South bound lanes.

Comp. decl. 16¾°E

continued next page

PRIMARY CORNER DESCRIPTION SE Cor. Redfield DLC #38 (Sec. 35)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

12/2006 per conversation between Randy Smith, DCSO & Medford BLM - BLM questioned 1953 renewal rec. S.89°14'30"E., 203.6' & East 59.4 ft. See C.S. 45/249

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21445-6)

Point for the SE cor. of DLC No. 38 at proportionate position, determined by the Grant Boundary method of adjustment, between P.O.C. marker STA 455 + 97.75 for the Old Pacific Highway and the Eastern most Northeast exterior cor. of DLC No. 38, from record information filed in the Douglas County Surveyor's Office per C.S. 45/249 and M9-19, there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 28" in the ground, with brass cap mkd.

T32S R6W

 DLC 38 | S 35

 2007

from which

A D.Fir, 5" dia., bears S.50°W., 356.6 ft., mkd. X at breast height and BT at the base.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

From this corner, the P.O.C. marker STA 455 + 97.75 for the Old Pacific Highway, set by person(s) unknown, perpetuated by the Douglas County Surveyor's Office in 1953 and 2005, recorded per files C.S. 45/249 and M9-19, and C.S. 67/10-21 respectively, bears, S.87°35'00"W., 261.80 ft. dist., monumented with an iron rod, ¾" dia., firmly set, projecting 5 ins. above the ground. This point now functions as a reference monument, from which bearing trees mkd. for the reference monument by the Douglas County Surveyor's Office in 2005

A D.Fir, 23" dia., bears N.80°E., 10.1 ft., with fragmentary scribe marks visible on partially healed upper and lower blazes.

A grand fir, 9" dia., bears S.65°E., 22.5 ft. with scribe marks RMCS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 038040

PRIMARY CORNER DESCRIPTION SE Cor. Redfield DLC #38 (Sec. 35)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A madrone, 10" dia., bears S.2 $\frac{3}{4}$ °E., 11.2 ft., with scribe marks RMCS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.

A madrone, 11" dia., bears S.83 $\frac{3}{4}$ °W., 28.6 ft., with scribe marks RMCS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.

At the corner point

Drive an aluminum cap, 2" dia., onto the rod, with aluminum cap mkd.

RM
DLC 38
261.8 FT
TO COR

From this reference monument, a 4" square wooden post painted white and marked SHRW and P.O.C. 455+97.75, bears NE, 0.4 ft.