

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & 36, T32-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8631)

Set ¼ sec. post on S. slope, from which
A Fir 6" dia., bears N.68°W., 27 lks. dist.
A Fir 30" dia., bears N.77°E., 18 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1861 (DCSO records Vol. 20 Page(s) 8657)

Old ¼ sec. cor. partially destroyed. Set a Laurel post 4 ft. long, 4" dia., 18" in the ground. Marked ¼ sec. on West side for the ¼ sec.cor. from which the old witness trees, yet standing are as follows, viz:
A Sugar Pine 10" dia., bears N.70°E., 25 lks. dist. mkd. ¼ S BT.
A Fir 36" dia., bears N.52°W., 26 lks. dist.

Douglas Co. Surveyors Office - John Powell and crew - June 25, 1969 - C.S. File 54/53-40

Found - Unrecorded 1" Iron rod, 1.0 ft. South of brass cap. "+" on log for ¼ corner.
10" Pine, now 34" stob, N.70°E., 16.5 ft. opened at a different time for scribe, scribe found "S" "1/"
36" D.Fir now burnt stump N.52°W., 17.2 ft.
Set Brass cap at cor. mkd: County Surveyors Office
R T 32 S R
7W S 36 | S 31 6W
1969
New BTs -11" Laurel N.16°W., 10.9 ft. mkd. "¼S36 CS BT"
17" S.Pine N.78°E., 34.6 ft. mkd. "¼S31 CS BT"
This corner lies about 50 ft. South of Robert Dollar Road.

Fd. BC & BTs by R. Wytcherly, 4/2008 - M156-10