

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T32-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8631-32)

-----  
Set ¼ sec. post, from which  
A Y.Pine 12" dia., bears N.50°W., 50 lks. dist.  
A Laurel 4" dia., bears N.78°E., 13 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1861 (DCSO records Vol. 20 Page(s) 8658)

-----  
Unable to find old cor. or witness trees. Set a Cedar post, 4 ft. long, 4" sq., 18" in ground. Marked ¼ S on W. side for the ¼ sec. cor., from which  
A Pine 54" dia., bears N.42°E., 76 lks. dist. mkd. ¼ S BT  
A Fir 8" dia., bears West, 39 lks. dist. mkd. ¼ S BT.

Survey by Wm. B. Paulin #552 - For: Holly A. Hough - July 1962 - C.S. File 51/239 and M 24-1

-----  
Found - Mound of stone at corner.  
38" Fir bearing West, 39 lks., very good scribe although core of tree rotten.  
Burnt Pine stump bearing N.42°E., 76 lks.  
Find ¼ marked on set stone in mound of stone.  
Set 2" x 36" Iron pipe and marked new BTs:  
P.Pine, 24" dia., bears S.88°30'W., 64.6 ft. mkd. ¼ S25 T32S R7W BT.  
Madrone, 10" dia., bears N.72½°E., 24.5 ft. mkd. ¼ S30 T32S R6W BT.

Fd. Ok by Gerald Nygren, 10/96, M 125-75  
Fd. OK by K. Hoffine, Jan. 2002 - M139-33