

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & 12 of T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8633)

Set ¼ sec. post, from which
A Fir 4" dia., bears N.55°W., 19 lks. dist.
A Laurel 3" dia., bears N.55°E., 26 lks.

GL0 survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1861 (DCSO records Vol. 20 Page(s) 8661)

Set a Fir post 4 ft. long, 4" sq., 20" in the ground, mkd. ¼ S on W. side for the ¼ sec. cor., from which
A Fir 24" dia., bears N.55°E., 12 lks. dist. mkd. ¼ S BT.
A Laurel 10" dia., bears S.70°W., 29 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Joe Brady, crew - Sept. 24, 1965 (added 6/7/2022)- C.S. File 49/91-16

(This report is typed written C.S. 49/91-16)

Found - 24" fir snag N.55°E., 7.9.

Tree has been opened no trace of scribe.

10" laurel S.70°W., 29.1.

Tree has been opened no trace of scribe.

Bearing of this tree is S.31°W. 21.5

Squared stake at cor scribed

¼S S12

Trees: 19" D.Fir S.87°W., 17.4

20" D.Fir S.14°E., 32.9

Trees are scribe but badly pitched over, can not read it.

Corner is about 2½ chains south of creek

Survey by Howard Johnstone - For: Roseburg Lumber - Feb. 1970 M 39-14

Set 5/8" Iron rod and alum. cap by proportionate measurement.
BTs - 12" D.Fir N.69 ¾°W., 24.1 ft.
8" D.Fir N.43¾°E., 9.5 ft.