

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8633-34)

Set post, cor. to secs. 6, 7, 1 and 12, near branch in ravine, from which

- A Fir 14" dia., bears S.44°W., 40 lks. dist.
- A Cedar 8" dia., bears N.57°W., 37 lks. dist.
- A Fir 16" dia., bears N.52°E., 22 lks. dist.
- A Cedar 6" dia., bears S.39°E., 26 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1861 (DCSO records Vol. 20 Page(s) 8661-62)

Set a Fir post 4½ ft. long, 4" sq., 22" in the ground, for the cor. to secs. 1, 6, 7 and 12, marked T32S R6W S6 on NE. face; S7 on SE. face; S12 on SW. face; T32S R7W S1 on NW. face. Also 5 notches on S. and one notch on N. angles of same, from which

- An Alder 8" dia., bears N.45°E., 58 lks. dist., mkd. T32S R6W S6 BT.
- An Alder 12" dia., bears S.55°E., 52 lks. dist., mkd. T32S R6W S7 BT.
- A Fir 30" dia., bears S.65°W., 23 lks. dist., mkd. T32S R6W S12 BT.
- A Fir 6" dia., bears N.48°W., 9 lks. dist., mkd. T32S R7W S1 BT.

Survey by Howard Johnstone - For: Roseburg Lumber - Feb. 1970 M 39-14

-
- Set 5/8" Iron rod with alum. cap.
 - BTs - 10" D.Fir N.68°E., 7.0 ft.
 - 10" D.Fir S.7 3/4°E., 37.2 ft.
 - 9" D.Fir S.45°W., 6.2 ft.
 - 21" D.Fir N.35½°W., 27.7 ft.

Fd. OK, March 1970 - DCSO JP C.S. File 54/36-106