

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 1 of T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8634)

-----  
Set ¼ sec. post, from which  
A Y.Pine 40" dia., bears N.89°W., 47 lks. dist.  
A Laurel 6" dia., bears N.80°E., 30 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1861 (DCSO records Vol. 20 Page(s) 8662)

-----  
(40.00 chs.)  
Set a Laurel post, 4 ft. long, 4" sq., 18" in the ground, mkd. ¼ S on W. side for the ¼ sec. cor., from which  
A Laurel 16" dia., bears S.80°E., 17 lks. dist. mkd. ¼ S BT.  
A Pine 4" dia., bears West, 32 lks. dist. mkd. ¼ S BT.  
(43.70 chs.)  
Old ¼ sec. cor. destroyed same and witness trees.

Survey by Howard Johnstone - For: Roseburg Lumber - Feb. 1969 M 33-49

-----  
Found - Orig. Bearing trees.  
Set 1" x 30" Iron pipe.  
Scribed -5" D.Fir N.88½°E., 26.7 ft.  
5" D.Fir N.81°W., 42.7 ft.

Mark Smalley, L.S. #2354 - For: Kenneth Ford - Oct. 1994 - M 121-7

-----  
Found - 1" iron pipe.  
7" Fir, N.81°W., 42.7'.  
6" Fir, N.88½°E., 26.7'.  
24" Laurel S.80°E., 11.2'.  
43" Pine, West, 21.1', snag OBT.  
New BT - 11" Fir, S.15°E., 18.2', scribed "¼ S BT"