

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Tsp. corner - Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7946)

Set post cor. to secs. 31 and 36 S. R. 6 and 7 W. on steep NE. slope, from which

A Fir 10" dia., bears S.64°E., 58 lks. dist.
Laurel 6" dia., bears S.25°W., 53 lks. dist.
Laurel 8" dia., bears N.37°W., 98 lks. dist.
Laurel 12" dia., bears N.78°E., 70 lks. dist.

Post and 4 BTs Fd. OK in GLO survey by W.H. Byars, under contract #448 dated June 13, 1882 (DCSO records, Vol. 19 Page 7951)

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Feb. 1969 - M 33-49

Set 5/8" x 30" Rod and alum. cap by double proportionate distance.

Scribed: 16" D.Fir S.28°W., 42.3 ft.
8" D.Fir S.43°E., 44.6 ft.
9" D.Fir N.57°W., 10.2 ft.
9" D.Fir N.72°E., 56.2 ft.

Survey by John H. Markham, Jr. - For: C & D Lumber Co. - Ray Brown, party chief, Jim Jenks, Witness - Jan. 6, 1986 - C.S. File 62/30-1

Found - 5/8" Iron rod with alum. cap mkd. properly.
9" D.Fir now 15" bears N.57°W., 10.2 ft. has good scar and is in good condition.
16" D.Fir now 25" bears S.28°W., 42.2 ft. has good scar and is in good condition.
8" D.Fir now 12" bears S.43°E., 44.6 ft. has good scar and is in good condition.
9" D.Fir now a 13" stump with 10" above ground, bears N.72°E., 56.2 ft.

New BT - 15" Madrona bears N.15°E., 65.1 ft. mkd. T31S R6W S31 BT.