

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8691)

-----  
Set a Chinquapin post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which

A Chinquapin 12" dia., bears N.10°E., 11 lks. dist., mkd. ¼ S BT.

A Fir 18" dia., bears S.36°W., 50 lks. dist., mkd. ¼ S BT.

Survey by Wm. Paulin - For: Robert Kischel - July 1962 - M 23-14

-----  
After diligent search, I set corner by proportionate measurement.

Set 1" x 36" Iron pipe at corner.

Marked 2 BTs:

6" Chinquapin bears N.21°W., 16.4 ft. dist., mkd. ¼ S19 T32S R6W BT.

8" Madrone bears S.27¼°E., 29.4 ft. mkd. ¼ S30 T32S R6W BT.