

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8698)

Set a Laurel post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S. on N. face, from which
A Pine 18" dia., bears N.10°E., 54 lks. dist., mkd 1/4 S BT.
A Laurel 14" dia., bears S.45°W. 4 lks. dist., mkd 1/4 S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy and T. Connell - June 22, 1965 - C.S. File 49/91-12

Found - Orig. 18" now 19" Pine, down, N.10°E., 35.6 ft., shows "1/4 S BT" scribe on unhealed scar.
No trace of other orig. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 6 W
1/4 S 6
S 7
1965

New BTs - 7" D.Fir N.20°W., 30.2 ft. mkd. 1/4 S 6 CS BT.
32" D.Fir S.58°E., 7.2 ft. mkd. 1/4 S 7 CS BT.

Mark Smalley, L.S. #2354 - For: Kenneth Ford - Oct. 1994 - M 121-7

Found - 1965 County BCIP.
10" Fir, N.20°W., 30.2', healed.
32" Fir, S.58°E., 7.2', healed.
New BTs- 9" Fir, N.5°W., 34.8', scribed "1/4 S BT"
10" Madrone, S.73°W., 8.3', scribed "1/4 S BT"
7" Alder, S.37°W., 15.2', scribed "1/4 S BT"