

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 143100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T33-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8639)

-----  
Set 1/4 sec. post on steep descent W., from which  
A Laurel 3" dia., bears S.33°E., 97 lks. dist.  
A Fir 15" dia., bears S.59°W., 117 lks. dist.

Richard L. Templin, Jr. - For: Superior Lumber Co. - March 11, 1958 - C.S. File 42/344

-----  
Found - 3" wood stake scribed "¼ S6" on South side.  
Orig. BT with scribing visible, S.59°W., 117 lks.  
Scribed -14" Fir N.48°W., 4.5 ft. mkd. "¼ S6 RE 3024 BT"

Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: M Pounds - July 29, 1964 - C.S. File 51/264

-----  
Found - Orig. post missing, found recent post in place.  
15" Fir bears S.59°W., 117 lks., now 49", scribes "14" visible.  
3" Laurel (Madrone) bears S.33°E., 97 lks., now 14" burnt stub, log down hill.  
R.L. Templin's post, from which a:  
12" Fir bears N.39°W., 5.0 ft. scribes ¼ S6 RE 3024 BT visible.  
Set 1½" x 36" galv. iron pipe with 3" brass cap mkd. "Ore. St. Bd. of Forestry ¼ S6 1964 RS 359", 33" in ground and from which a:  
15" Fir bears S.2°W., 35.8 ft. scribed ¼ S6 BT.  
12" Fir bears N.49°E., 12.3 ft. scribed RS 359.  
Set 3" round x 5 ft. alum. painted fir post, 1.0 ft. NW of corner pipe. Ore. St. Forestry Dept. metal location poster on above 12" Fir.

Fd. OK, August 1990, M 112-41

Fd. OK, G. Nygren, March 1994, M 118-79