

PRIMARY CORNER DESCRIPTION So. Cor. for Secs. 31 and 32 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8643)</p> <p>-----</p> <p>Set post cor. to secs. 31 and 32, from which A Laurel 24" dia., bears N.15°E., 7 lks. dist. A Laurel 8" dia., bears N.20°W., 30 lks. dist.</p>
<p>Wallace Owen - Asst. Engineer - For: Robert Dollar Co. - April 18, 1958 - C.S. File 42/354</p> <p>-----</p> <p>Found - Corner in poor condition, from which Orig. 24" Laurel N.15°E., 7 lks., now missing Orig. 8" Laurel N.20°W., 30 lks. now a rotten stub Set the corner from the 8" Laurel using compass and chain. Drove a 7/8" rod and scribed: 6" Laurel N.26°30'W., 18.1 ft. "S31 RS 424 BT" 5" Laurel N.28°30'E., 32.3 ft. "S32 RS 424 BT"</p>
<p>Survey by Victor McLind - For: John Clive - Nov. 1975 M 58-57</p> <p>-----</p> <p>Rod missing. Set 2" x 2" Hub at corner, from which 6" Laurel now 10", bears N.26½°W., 18.1 ft., scribes partially visible. 5" Laurel now 9", bears N.28½°E., 32.3 ft., scribes partially visible.</p>
<p>Fd. BTs OK, April 1984, R. Thompson, RM 3-61</p>
<p>Survey by Max Hull - For: Gregory Forest Products - August 1990 - C.S. File 63/115 and M 112-14</p> <p>-----</p> <p>Found - 13" dia. Madrone N.26½°W., 18.1 ft. blaze healed. 12" dia. Madrone N.28½°E., 32.3 ft. blaze healed. Set 5/8" I.R. w/cap mkd. "Hull R.S. 901". I.R. 30" long. New BTs -10" D.Fir S.58°E., 34.0 ft. scribed. 8" D.Fir S.23°W., 24.7 ft. scribed.</p>
<p>Douglas County Surveyors Office - Randall Smith &amp; Stephen Flause - 9/15/96 - C.S. 64/66-9</p> <p>-----</p> <p>MON. Fd.- 5/8" I.R. protruding 3" above ground Bt's Fd.- 12" dia. Madrone, with a fully healed double blaze, bears N.33½°W., 18.1'. 11" dia. Madrone, with a fully healed double blaze, bears N.26°E., 32.3'.  (Cont. Next Page)</p>

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION So. Cor. for Secs. 31 and 32 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

14" dia. D.Fir, with a partially healed double blaze, scribing visible "S BT" , bears S.58°E., 34'.

10" dia. D.Fir with a partially healed double blaze, scribing visible "3 RS 90 BT", bears S.23°W., 24.7'.

Mon. Set - 5/8" I.R. is referenced a 2 3/8" Dia. DCSO Brass cap on a 1 3/8" O.D. by 32" long Iron Pipe is set a referenced position. BC/IP protrudes 6" above ground.

5/8" I.R. measured 31½" long is set along north edge of BC/IP, protruding 4" above ground.