

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8655)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.16°W., 34 lks. dist.
A Fir 9" dia., bears S.67°E., 14 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dec. 1955 - C.S. File 47/42

Found - Orig. 18" R.Fir scribed ¼ S bears N.21°45'W., 23.1 ft.
Orig. 18" Fir bears S.62°05'E., 8.6 ft.
Set an Iron pipe with brass cap mkd: ¼ S 31|32 T32S R6W
County Surveyors Office 1956.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Oct. 1967 - C.S. File 54/53-26

Found - DCSO brass cap 1955, properly mkd.
18" D.Fir now stob 12" high, N.21½°W., 23.1 ft. Tree has been opened, scribe visible "4 S"
18" now 19" D.Fir N.15°W., 27.8 ft., pitched over, scribe visible.
Orig. 9" now 20" D.Fir S.63°E., 8.6 ft. (Rec. S.67°E., 9.2 ft.), shows scar.
Reblazed and rescribed:
20" D.Fir S.63°E., 8.6 ft. mkd. ¼ S32 CS BT.