

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8655)

Set post cor. to secs.29, 30, 31 and 32, from which
A W.Oak 20" dia., bears N.31°W., 139 lks. dist.
A W.Oak 9" dia., bears S.13°E., 73 lks. dist.
A B.Oak 18" dia., bears N.76°E., 65 lks. dist.
A B.Oak 15" dia., bears S.30°W., 176 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8688-89)

The corner post being destroyed, I re-establish same as per notes furnished. Bearing trees allstanding, viz: Set a post 4 ft. long, 4" sq., 24" in the ground, for the cor. marked T32S R6W S29 on NE.; S32 on SE.; S31 on SW.; S30 on NW. faces with 1 notch on S. and 5 notches on East edges, from which
An Oak 18" dia., bears N.76°E., 65 lks. dist., mkd. T32S R6W S29 BT.
An Oak 9" dia., bears S.13°E., 73 lks. dist., mkd. T32S R6W S32 BT.
An Oak 15" dia., bears S.30°W., 176 lks. dist., mkd. T32S R6W S31 BT.
An Oak 20" dia., bears N.31°W., 139 lks. dist., mkd. T32S R6W S30 BT.

Fd. Sec. cor. mkd. with a 3/4" Iron rod, D.F. Thenno, Dec. 1951, C.S. File 40/395

Survey by A.R. Evans - 1953 - C.S. File 41/241

Found 3/4" iron rod in mound of rock.

Survey by Norman D. Price - For: Dollar and Patterson Co. Inc. Nov. 1954/May 1955 - C.S. File 41/375

This corner is monumented with an iron rod, 3/4" dia., firmly set in a mound of stone, it is locally used and accepted but there is no remaining evidence of the original corner monument.

At the corner point, over the iron rod, Set an iron pipe, 3 ft. long, 2" dia., 28" in the ground, mkd. RS33 - and mark new bearing trees as follows:

A Madrona 6" dia., bears N.39°E., 73 lks. dist., mkd. T32S R6W S29 RS33 BT.

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A Fir 6" dia., bears S.8°E., 38 lks. dist., mkd. T32S R6W S32 RS33 BT.

A Fir 11" dia., bears S.64°W., 24 lks. dist., mkd. T32S R6W S31 RS33 BT.

A Fir 18" dia., bears N.67°W., 29 lks. dist., mkd. T32S R6W S30 RS33 BT.

The geographic position of this corner is latitude 42°45'13"N., and longitude 123°26'50"W. The observed magnetic declination is 20°57'E.

Fd. Ok by Gerald Nygren, 10/96, M 125-75
Fd. OK by K. Hoffine, Jan. 2002 - M139-33

DCSO-GIS Corner visitation - 2/19/2004 - Typed: 2/10/2011 -
C.S. File 67/33-1

Monument - 2"
Comment - needs renewal