

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8689)

-----  
Set a Laurel post 3 ft. long, 3" sq., 20" in the ground for 1/4 sec. cor. marked 1/4 S. on W. face, from which

A Laurel 6" dia., bears N.86°E., 34 lks. dist., mkd. 1/4 S BT.

A Laurel 5" dia., bears S.66°W., 16 lks. dist., mkd. 1/4 S BT.

Survey by Norman D. Price, LS #33 - For: Dollar and Patterson Co. Inc. - Nov. 1954/May 1955 - C.S. File 41/375

-----  
Corner set at proportionate distance; there is no remaining evidence of the original corner.

Set an iron pipe 3 ft., 1 1/2" dia., 28" in the ground, mkd. RS33, from which

A Fir 16" dia., bears N.13°E., 32 lks. dist., mkd. 1/4 S29 RS33 BT.

A Fir 12" dia., bears S.45°W., 19 lks. dist., mkd. 1/4 S30 RS33 BT.

Fd. Ok by Gerald Nygren, 10/96, M 125-75  
Fd. OK by K. Hoffine, Jan. 2002 - M139-33

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 1/2015 - C.S. File 65/87-5

-----  
Found - 1 1/4" iron pipe  
46" D.Fir N.13°E., 21.1 good scar  
31" D.Fir stump S.45°W., 12.5 ft. healed scar.  
New - 7" fir S.79°E., 22.7 ft. scribed 1/4 S29 BT.  
7" chinquapin N.14°W., 5.2 ft. scribed 1/4 S30 BT.  
Compass decl. 15 1/2°E.