

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8689)

-----  
A Laurel 6" dia., which I marked T32S R6W S20 on NE.; S29 on SE.; S30 on SW.; and S19 on NW. faces with 2 notches on S. and 5 notches on East edges, from which

A Laurel 6" dia., bears N.30°E., 18 lks. dist., mkd. T32S R6W S20 BT.

A Chinquapin 5" dia., bears S.40°E., 16 lks. dist., mkd. T32S R6W S29 BT.

A Laurel 6" dia., bears S.48°W., 20 lks. dist., mkd. T32S R6W S30 BT.

A Laurel 6" dia., bears N.65°W., 18 lks. dist., mkd. T32S R6W S19 BT.

Survey by Norman D. Price, LS #33 - For: Dollar and Patterson Co. Inc. - Nov. 1954/May 1955 -C.S. File 41/375

-----  
The locally recognized and accepted cor. of secs. 19, 20, 29 and 30 at corner of burned fences extending N., E., and S. The fence corner post is marked with incomplete burned scribe marks. There is no evidence of the original corner monument. I accept this position as the most acceptable evidence of the original corner.

Against the E. side of fence corner post, set an iron pipe, 3 ft. long, 2" dia., 28" in the ground, mkd. RS33.

I mark new bearing trees as follows:

A Madrona 6" dia., bears N.84½°E., 102 lks. dist., mkd. T32S R6W S20 RS33 BT.

A Chinquapin 6" dia., bears S.57°E., 69 lks. dist., mkd. T32S R6W S29 RS33 BT.

A Chinquapin 6" dia., bears S.48°W., 30 lks. dist., mkd. T32S R6W S30 RS33 BT.

A Madrona 6" dia., bears N.38½°W., 42 lks. dist., mkd. T32S R6W S19 RS33 BT.

James McIntosh, surveyed for State of Oregon, Dept. of Forestry; April 2000 - M134-80

-----  
Found OK as above CS File 41/375.

Set - Orange carsonite marker, CBM 250 labeled witness post bears N.56°E., 2.70 ft. to base.

Set - Orange carsonite marker, CBM 250 labeled witness post bears N.49°W., 3.25 ft. to base.

Fd. IP & BTs per renewal, 3/2013 - by G. Nygren, M165-1