

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8691)

Set a Laurel post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Laurel 8" dia., bears N.75°E., 10 lks. dist., mkd. ¼ S BT.
A Laurel 12" dia., bears N.75°W., 22 lks. dist. mkd. ¼ S BT.

Survey by Lloyd D. Smith - For Oregon Dept. of Forestry - May 25, 1978 - M 71-79

Set 12" Fir corner tree with yellow metal location poster.
New BTs -12" Fir bears S.35°E., 36.7 ft. RS 1101 with yellow metal location poster.
16" Fir bears S.50½°W., 39.8 ft.
4" x 4" x 72" white painted cedar post bears N.49°E., 4.1 ft.

James McIntosh, surveyed for State of Oregon, Dept. of Forestry; April 2000 - M134-80

Set - Orange carsonite marker, CBM 250 labeled witness post bears N.82°E., 4.8 ft. to base.
Set - Orange carsonite marker, CBM 250 labeled witness post bears N.48°W., 4.3 ft. to base.