

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8692)

Set a Yew post 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 17, 18, 19 and 20, marked T32S R6W S17 on NE.; S20 on SE.; S19 on SW.; and S18 on NW. faces with 3 notches on S. and 5 notches on East edges, from which
A Maple 12" dia., bears N.82°E., 21 lks. dist., mkd. T32S R6W S17 BT.
A Maple 8" dia., bears S.85°E., 26 lks. dist., mkd. T32S R6W S20 BT.
A Fir 16" dia., bears S.82°W., 10 lks. dist., mkd. T32S R6W S19 BT.
A Fir 12" dia., bears N.60°W., 23 lks. dist., mkd. T32S R6W S18 BT.

Not Fd by VRT, crew & Or. St Forestry crew, 4/4/1969 (added (3/28/2017) C.S. File 54/53-36: AS per location pointed out by Or. St. Forestry. No trace of OBTs.

Survey by Lloyd D. Smith - For: Oregon Dept. of Forestry - May 25, 1978 - M 71-79

Set Oregon State Board of Forestry 1½" x 36" galv. I.P. with 3" bronze cap 26" in ground in mound of rock.
BTs - 15" Fir bears N.07½°W., 10.0 ft. RS 1101.
10" Fir bears S.65°W., 40.7 ft.
14" Fir bears S.20°E., 6.2 ft. with yellow metal location poster.
17" Fir bears N.49°E., 55.4 ft.
4" x 4" x 72" white painted cedar post bears S.42°W., 3.8 ft.

Fd. OK, Greg Lang - Aug. 1989 - M122-47