

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8699)

-----  
Set a Cedar post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S. on W. face, from which  
A Maple 5" dia., bears N.40°E., 19 lks. dist. mkd. 1/4 S BT.  
A Fir 28" dia., bears N.54°W., 18 lks. dist., mkd. 1/4 S BT.

BLM resurvey by G. Steven Popken, Cadastral Surveyor, under Group #883, surveyed Sept. 8-25, 1975 - (DCSO records, Vol. 37 Pgs 15379-80)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 32 S R 6 W  
1/4  
S 6 S 5  
1975

from which

A Fir 21" dia., bears N.66°E., 39 1/2 lks. dist., mkd. 1/4 S5 BT.

A Fir 30" dia., bears S.50 1/2°W., 72 1/2 lks. dist., mkd. 1/4 S6 BT.

From this point, an iron pipe 1/2" dia., firmly set, projecting 6" above ground, bears N.70 1/4°E., 0.208 chs. dist.

Mark Smalley, L.S. #2354 - For: Kenneth Ford - Oct. 1994 - M 121-7

-----  
Found - 1975 Cadastral BCIP

24" Fir, N.66°E., 26.1', healed.

32" Fir, S.50 1/2°W., 47.9', healed.

New BTs- 6" Chinquapin, N.66°W., 14.7', scribed "1/4 BT".

24" Fir, N.59°E., 14.9', scribed "1/4 BT".