

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8643)

Set ¼ sec. post on N. slope, from which
A Fir 20" dia., bears N.53°W., 24 lks. dist.
A Fir 18" dia., bears N.38°E., 9 lks. dist.

G.J. Wenderoth - Jeane Richardson - Feb. 1942 - C.S. File 16/55

1/2" x 30" galv. iron pipe.
28" Fir N.24°12'W., 31.8 ft. (New)
20" Fir stump, N.21°E., 7.5 ft. (O.B.T)

G. Wenderoth, N. Richardson - April 1942 - C.S. File 16/55 (and "old" corner book, page 172)

Found - 1/2" x 30" galv. iron pipe.
Stump of original BT, N.21°E., 7.5 ft.
Set new BT:
28" Fir N.24°12'W., 31.8 ft.

A.R. Evans - 1953 - C.S. File 41/241

Found - 1/2" iron rod.
28" Fir N.24°12'W., 31.8 ft.
Blazed and scribed:
6" Fir N.70°E., 10.2 ft.

Cor. Fd. OK, DCSO, James Byron, Dec. 16, 1955, C.S. File 47/42 and M 1-1

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Sept/Oct. 1967 - C.S. File 54/53-9

Found - 6" now 8" D.Fir N.70°E., 10.2 ft., shows good scar
28" D.Fir, now stump, N.24°W., 31.8 ft., faint bark scribe "BT".
1/2" I.Pipe at ¼ corner.
New BT - 10" D.Fir N.84°W., 36.2 ft. mkd. ¼ S32 CS BT.
This corner lies 198 ft. West of ¼ cor. to Sec. 5 only, T33-6

Fd. OK, Aug. 1990, M 112-14