

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Section 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyors Office - James W. Byron, Deputy -
Dec. 1955 - C.S. File 47/42 and M 1-1

Set at intersection of lines run from S ¼ corner to N. ¼
corner and E ¼ corner to W ¼ corner.

Set Witness corner since Center ¼ corner falls in Blevin's
yard.

Set iron pipe with brass cap for Witness corner, 40.5 ft.
North of true center ¼ cor. and mkd. "Wit. Cor. C¼ cor. S32
40.5' S. to C ¼ cor., T32S R6W County Surveyors Office 1956".

Blazed and scribed two trees:

48" W.Oak S.47°E., 40.2 ft. mkd. Wit. Cor. C¼ S32 CS BT

20" Cedar North, 87.8 ft. mkd. Wit. Cor. C¼ S32 CS BT.

Survey by Ronald Brandt - For: Chadwick - Aug. 1972 - M 46-46

Reset brass cap wit. center ¼ cor. of sec. 32, (reset 40.5
ft. N.0°54'30"E., from center) from which bears

23.2" Incense Cedar N.02°17'E., (North) 87.8 ft. scribed.

Stump of 48" W.Oak S.55°22'E., (S47°E) 40.2 ft.,
overgrowth on destroyed scribing used to establish face
position.

Fd. OK, August 1990, M 112-14