

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8690)

Set a Cedar post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec cor. marked 1/4 S. on N. face, from which
A Fir 10" dia., bears N.80°E., 48 lks. dist. mkd. 1/4 S BT.
A Laurel 12" dia., bears S.54°E., 18 lks. dist., mkd. 1/4 S BT.

Survey by Norman D. Price, LS #33 - For: Dollar and Patterson Co. Inc., - Nov. 1954/May 1955 - C.S. File 41/375

Determined at the record bearing and distance from both old bearing trees.
At the corner point,
Set an iron pipe, 3 ft. long, 1 1/2" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:
A Fir 18" dia., bears N.80°E., 48 lks. dist., with blaze burnt.
A Madrona 18" dia., bears S.54°E., 18 lks. dist., with blaze decayed.
And new bearing trees:
An Incense Cedar 14" dia., bears N.17°E., 76 lks. dist., mkd. 1/4 S20 RS33 BT.
A Fir 10" dia., bears S.23°E., 46 lks. dist., mkd. 1/4 S29 RS33 BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #910 Surveyed, Aug/Sept. 1976 - (DCSO records Vol. 41 Page(s) 16323-24)

The 1/4 sec. cor., perpetuated and recorded by Price in 1954-55, from original evidence no longer in existence, monumented with an iron pipe 1 1/2" dia., firmly set, projecting 12" above ground, mkd. RS 33, from which bearing trees mkd. by Price:
A Cedar 22" dia., bears N.17°E., 73 1/2 lks. dist., with healed blaze.
A Fir 15" dia., bears S.23°E., 45 1/2 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 21 ins. in the ground, directly over iron pipe, with brass cap marked
T 32 S R 6 W
1/4 S 20
S 29
1976