

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8697)

Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
A Fir 20" dia., bears N.50°E., 31 lks. dist., mkd. ¼ S BT.
A Fir 24" dia., bears S.60°E., 27 lks. dist., mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon Dept. of Forestry - Oct. 15, 1974 - M 54-60

Set Oregon State Board of Forestry 1½" x 36" Galv. I.Pipe with 3" bronze cap 34" in ground, in mound of rock.
BTs - 14" Fir S.36°W., 155.8 ft.
36" Fir N.02°E., 20.1 ft. with yellow metal location poster.
4" x 4" x 72" white painted cedar post S.26°E., 8.0 ft.

Cor. Fd. and used in BLM resurvey by G. Steven Popken, under Group #883, surveyed Sept. 1975 (DCSO records, Vol. 37 Page 15378)