

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8652)

-----  
Set ¼ sec. post on S. slope of mountain, from which  
A W.Oak 20" dia., bears N.83°W., 353 lks. dist.  
A W.Oak 18" dia., bears N.40°E., 170 lks. dist.

J. W. Cole, N.E. Richardson - Survey for: Snyder - July 1923  
Vol. 3 Pg. 162; C.S. File 7/5B (and "old" corner book, pg. 1)

-----  
I renewed this corner from the burned out stump of old BT, N.83°W., 353 lks. Also, hole where other BT had stood bears N.40°E., 170 lks. Fences corner at the place located from trees.  
I set a 1½" x 24" galv. Pipe and erected mound of rock. Marked two points of ledge rock for bearing objects:  
N.45°W., 11.2 ft.  
N.21°30'E., 40.8 ft.

1½" I.P. Fd. OK, DCSO, J. Byron, Dec. 1955, C.S. File 47/42 and M 1-1

George J. Wenderoth, Deputy - Dec. 6, 1964 - C.S. File 49/8-3

-----  
Found - Ledge rock N.45°W., 11.2 ft., "X" and "CS" cut in rock.  
Ledge rock N.21°30'E., 40.8 ft., "X" cut in rock.  
1½" I.Pipe badly bent. Remove and replace with:  
Set Brass cap at cor. mkd: County Surveyors Office  
¼ Sec. 32 & 33 L.S 5

Douglas Co. Surveyors Office - R.B. Kimberling, Deputy, P.L. Earle, crew - Feb. 21, 1978 - C.S. File 59/46-27

-----  
Found - 1" I.P. with brass cap set 0.1 ft. below ground and marked: "County Surveyors Office 33 32 1/4c Dep LS 5." Brass cap is at corner of old wire fence, N-S and E-W.  
Rock outcropping bears N.45°W., 11.2 ft. with chiseled "+" and "CS".  
Rock outcropping bears N.21½°E., 40.3 ft. (Rec. 40.8 ft.) with chiseled "+".  
NO NEW MONUMENT SET.  
New Accessories:  
10" D.Fir bears N.17°W., 33.1 ft. double blazed and scribed "¼ S32 CS BT"  
(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fence post which is at the end of a wire fence to the North, bears N.77°W., 6.3 ft.
Fd. OK, Aug. 1990, M 112-14
Bruce Shaner, L.S. 430 - For: Superior Lumber - 10/96 - M 124-28 - C.S. File 65/8-9 ----- Found - DCS0 1964 brass cap. 12" D.Fir, now down & dead, bears N.17°W., 33.1'. New accessories - 12" Madrona I scribed "¼ S33 BT" bears S.18°E., 5.6' 10" Oak, I scribed "¼ S32 BT" bears N.40°W., 10.1'. 6' steel fence post, I set, bears North 1.0'. 6' steel fence post, I set, bears South 1.0'. Note - Corner lies North, 150' from old Robert Dollar Timber Access road. Dec. 20° E.
Fd. OK - R. Wytcherley - Jan. 1997 - M 126-47 Fd. OK by R. Wytcherley, July 2001 - M137-18 Fd. OK by R. Wytcherley, July 2006 - M151-31 Fd. as per renewal 11/2012 - M164-44 by R. Brown