

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8653)

Set ¼ sec. post, from which
A B.Oak 8" dia., bears N.89°E., 56 lks. dist.
A Cedar 11" dia., bears S.66°W., 57 lks. dist.

Survey by Norman D. Price, L.S. #33 - For: Dollar and Patterson Co. Inc. - Nov. 1954/May 1955 - C.S. File 41/375

Determined at the record bearing and distance from each old original bearing tree.

At the corner point
Set an iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:

The badly decayed stump of a B.Oak bears N.89°E., 56 lks. dist.

An Incense Cedar 28" dia., bears S.66°W., 57 lks. dist. with partial scribe marks on charred face of old blaze.

and new bearing trees:

A Fir 36" dia., bears S.38°E., 18 lks. dist., mkd. ¼ S28 RS33 BT.

A Chinquapin 6" dia., bears S.28°W., 49 lks. dist., mkd. ¼ S29 RS33 BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #910 Surveyed, Aug/Sept. 1976 - (DCSO records Vol. 41 Page(s) 16317)

The sec. cor., perpetuated and recorded by Price in 1955, monumented with an iron pipe, 1½ dia., firmly set, projecting 4" above ground, from which the remains of an original bearing tree:

A Cedar stump 28" dia., bears S.66°W., 51 lks. dist., with charred blaze, no mark visible.

and the remains of bearing trees mkd. by Price

A Fir snag 41" dia., bears S.38°E., 18 lks. dist., with scribe marks ¼ S28 RS 33 BT visible on open blaze.

A Tan Oak 7" dia., bears S.28°W., 49 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, directly over iron pipe, with brass cap marked

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>T 32 S R 6 W ^¼ S 29 S 28 1976</p> <p>from which new bearing trees: A Fir 10" dia., bears N.13¼°E., 57 lks. dist., mkd. ¼ S28 BT. A Fir 12" dia., bears S.65°W., 116 lks. dist., mkd. ¼ S29 BT.</p>
<p>Fd. OK, Jan. 1991, M 111-34</p>
<p>Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, Deputies - Jan. 16, 1992 - C.S. File 64/23-3 ----- Found = 1976 3¼" dia. brass cap on a 2½" O.D. iron pipe, protruding 5" above ground. (BLM) Orig. Cedar S.66°W., 37.6 ft., now gone. 36" now 36" dia., 12 ft. high burnt and rotting D.Fir snag, no scribing or blazes visible, bears S.38°E., 11.9 ft. (agrees w/rec.) 6" now 9" dia., 6 ft. high, Tan Oak stump with a fully healed single blaze, bears S.28°W., 33.3 ft. 12" now 13" dia., 5 ft. high D.Fir stump with a fully healed single blaze bears S.65°W., 76.6 ft. (1976 BLM BT.) 10" now 13" dia. dead D.Fir with a fully healed single blaze bears 30° might be where the distance problem came from. (an unreduced slope distance in ft.) New BTs -3" dia. D.Fir double blazed and scribed "X BT" bears N.74°E., 38.0 to center of trunk at upper blaze. 10" dia. Tan Oak bark scribed "¼ S28 CS BT" bears S.89½°E., 32.0 ft. Corner lies on a North-South cut line on a SE slope.</p>
<p>Adam DeGroot - For: Silver Butte Timber Co. - Oct. 2016 - M171-19 ----- Found - A 2½" iron post by US BLM cadastral surveyors Roseberry & Aanrud in 1976 per Vol. 41, PG 16317, firmly set and projecting 6" above ground, w/a properly mkd. 3¼" brass cap per record: From which the 1992 DCSO BTs: A 13" D.Fir bears N.75°15'E., 38.4 ft, with healed dbl blaze (N.74°E., 38.0 ft) continued next page</p>

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 12" tan oak bears S.87°45'E., 31.7 ft, w/bark
scribe visible (S.89½'E., 32.0 ft)
and new references:
A 8" D.Fir bears S.35°45'W., 16.4 ft scribed "¼ S29
BT"
A mag-hub & brass washer in base of a 13" live oak
bears N.37°02'W., 15.71 ft.
NAD 83 (CORS 96)
Lat: 42°45'41.10389"N Long: 123°25'35.52864"W