

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8654)

Set post cor. to secs.20, 21, 28 and 29, from which
A Laurel 12" dia., bears S.45°W., 18 lks. dist.
A Laurel 10" dia., bears S.63°E., 27 lks. dist.
A Laurel 9" dia., bears N.59°E., 17 lks. dist.
A Laurel 9" dia., bears N.20°W., 19 lks. dist.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #910 Surveyed, Aug/Sept. 1976 - (DCSO rec Vol. 41 Pg 16318)

The sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 32 S R 6 W
S 20 | S 21
S 29 | S 28
1976

from which
A Fir 13" dia., bears N.60½°E., 30 lks mkd T32S R6W S21 BT
A Fir 10" dia., bears S.80°E., 159 lks mkd T32S R6W S28 BT
A Fir 6" dia., bears S.71½°W., 69½ lks mkd T32S R6W S29 BT
A Fir 16" dia., bears N.9½°W., 16½ lks mkd T32S R6W S20 BT

Adam DeGroot - For: Silver Butte Timber Co. - Oct. 2016 - M171-19

Found - A 2½" iron post by US BLM cadastral surveyors Roseberry & Aanrud in 1976 per Vol. 41, PG 16318, firmly set and projecting 6" above ground, w/a properly mkd. 3¼" brass cap per record:
From which bearing trees by Roseberry in 1976:
A 23" D.Fir bears N.60°15'E., 19.2 ft w/healed blaze (N.60½°E., 30 lks)
A 12" D.Fir snag bears S.80°30'E., 105.0 ft w/healed blaze (S.80°E., 159 lks)
A 16" D.Fir bears S.71°15'W., 46.0 ft in/healed blaze (S.71½°W., 69.5 lks)
A 24" D.Fir bears N.10°30'W., 10.0 ft w/healed blaze (N.9½°W., 16.5 lks)
And a new bearing tree:
A 14" D.Fir bears S.60°45'E., 12.4 ft scribed "T32SR6WS28BT"
NAD 83 (CORS 96)
Lat: 42°46'07.16637"N Long: 123°25'35.19194"W