

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8684-85)

Set a Yew post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 8, 9, 16 and 17, marked T32S R6W S9 on NE.; S16 on SE.; S17 on SW.; and S8 on NW. faces, with 4 notches on S. and E. edges, from which

A Fir 8" dia., bears N.55°E., 68 lks., mkd. T32S R6W S9 BT

A Fir 10" dia., bears S.38°E., 15 lks. dist., mkd. T32S R6W S16 BT.

A Dogwood 10" dia., bears S.38°W., 82 lks. dist., mkd. T32S R6W S17 BT.

A Fir 20" dia., bears N.5°W., 82 lks., mkd. T32S R6W S8 BT

Douglas County Surveyors Office - James Byron, Deputy, S.A. Bilow, Milo Godfrey, crew - June 12, 1959 - C.S. File 49/91-6

Found - Orig. 10" now 18" Fir S.38°E., 9.9 ft. shows good scar, I do not open.

Orig. 20" now 29" Fir N.5°W., 54.1 ft. shows good bark scribing "T32 S B".

Orig. 8" now 10" down Fir N.55°E., 44.9 ft. shows good scribing.

No trace of orig. SW BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 6 W

S 8 | S 9

S17 | S16

1959

New BTs -9" R.Fir bears S.27½°W., 60.5 ft. scribed S17 T32S R6W CS BT.

6" Hemlock bears N.66°E., 16.8 ft. scribed S9 CS BT.

6" Hemlock bears N.45°W., 12.4 ft. scribed S8 CS BT.

Fd. OK, DCSO, J.Powell, Sept. 1967 C.S. File 54/53-22

Cor Fd & used in BLM resurvey by Lynn Roseberry, under Contract #910, surveyed Aug/Sept. 1976 (DCSO rec, Vol. 41 pg 16322-23

David Edwards - For: Swanson Group, Inc. - 10/2003 - M 143-23

Found - Brass cap
25" Fir S.38°E., 9.9 ft.

8" Chinq. S.5°E., 54.1 ft.

New BT - 8" Chinq. S.20°E., 30.75 ft. scribed "S16 BT"

6' steel post East 2'

Fd. DCSO brass cap & BTs, by G. Nygren 5/2012 - M163-56