

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8686-87)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 4, 5, 8 and 9, marked T32S R6W S4 on NE.; S9 on SE.; S8 on SW.; and S5 on NW. faces, with 5 notches on S. and 4 notches on East edges, from which
A Chinquapin 12" dia., bears N.50°E., 27 lks. dist., mkd. T32S R6W S4 on NE.
A Fir 36" dia., bears S.40°E., 31 lks. dist., mkd. T32S R6W S9 BT.
A Laurel 8" dia., bears S.60°W., 30 lks. dist., mkd. T32S R6W S8 BT.
A Pine 36" dia., bears N.40°W., 35 lks. dist., mkd. T32S R6W S5 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Sept. 26, 1967 - C.S. File 54/53-7

Found - 36" now 42" Pine, N.48°W., 23.1 ft. old scribe "R6", newer scribing in wood approx. 42 years ago, "T32 5 BT".
No trace of other BTs.
16" D.Fir N.58°E., 21.8 ft., scribed T32S R6W S4 BT, un-recorded.

Set Brass cap at cor. from 42" Pine mkd:
County Surveyors Office
T 32 S R 6 W
S 5 | S 4
S 8 | S 9
1967

New BTs -5" Laurel S.74°W., 24.2 ft. mkd. T32S R6W S8 CS BT
6" Chinquapin S.52½°E., 12.2 ft. mkd. T32S R6W S9 CS BT.

Douglas Co. Surveyors Office - Gary Langlitz, Deputy - P.Earle, crew - March 28, 1974 - C.S. File 56/49-8

Found - 1967 DCSO brass cap properly mkd., out of the ground I add the markings "1974" to the brass cap and set it at the record bearing and distance from an orig. 36" now 46" Pine snag BT with scribing "2 S 5 T" visible on previously opened blaze. Powell in 1967, calls for bearing to the NW orig. Pine BT, to be N.48°W. The orig. survey notes call for N.40°W. I set the brass cap at the orig. bearing and distance of N.40°W., 23.1 ft. from this Pine BT. (Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 36" now 46" Pine snag bears N.40°W., 23.1 ft. with marks showing as noted above.
5" now 6" Madrone bears S.74°W., 20.0 ft. (S.74°W., 24.2 ft.) with scribing "S 8 BT" visible.
6" now 7" Chinquapin bears S.59½°E., 14.2 ft. (S.52½°E., 12.2 ft.) with scribing "T32S R6W S9 CS BT"
16" now 18" D.Fir bears N.62°E., 23.6 ft. (N.58°E., 21.8 ft.) with scribing "2 6 W S4 BT" visible.
New BT - 22" D.Fir bears N.29½°W., 62.2 ft. scribed "T32S R6W S5 CS BT".

Cor. Fd. and used in BLM resurvey by G. Steven Popken, under Contract #883, surveyed Sept. 1975 - (DCSO records, Vol. 37 Pages 15375-76)