

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8688)

Set a Cedar post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S. on W. face, from which
A Fir 30" dia., bears N.30°E., 26 lks. dist., mkd. 1/4 S BT.
A Fir 20" dia., bears N.15°W., 34 lks. dist., mkd. 1/4 S BT.

Douglas Co. Surveyors Office - J Powell & Crew - 9/1967
(added 10/19/2016) - C.S. File 54/53-8

Not fd?
Found - 30" fir now 38" N.30°E., 17.2, 1/4 put on with axe.
20" fir now 29" N.15°W., 22.4, 1/4 put on with pocket knife.
No orig. scribe fd. Both trees tagged by BLM? Harris
- W. Owens.

Douglas Co. Surveyors Office - Gary Langlitz, Deputy, P. Earle crew - Nov. 5, 1974 - C.S. File 57/12-2

Found - An orig. 30" now 44" D.Fir bearing N.30°E., 17.2 ft. We find a faint "BT" scribed in the bark. Also a "1/4" chopped in the bark but it is not an orig. marking.
An orig. 20" now 34" D.Fir bearing N.15°W., 22.4 ft. We find faint bark scribing "1/4 BT".
At the corner point We set a 1" x 30" I.P. with brass cap attached mkd: County Surveyors Office
T 32 S
S 5 | S 4
1/4
R6W
1974
New BTs -30" D.Fir bears S.53°W., 33.5 ft. scribed "1/4 S5 CS BT."
12" Yew bears S.74°E., 36.2 ft. scribed "1/4 S4 CS BT"

Cor. Fd. and used in BLM resurvey by G. Steven Popken, under Group #883, surveyed Sept. 1975, (DCSO records, Vol. 37 Pages 15376-77)