

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8684)

Set a Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Cedar 30" dia., bears S.20°E., 39 lks. dist., mkd. ¼ S BT.
A Cedar 24" dia., bears N.57°W., 46 lks. dist., mkd. ¼ S BT.

Survey by Ronald Brandt - For: Robert Dollar Co. - July 27, 1970 - C.S. File 55/129-2

Found - 36" Incense Cedar S.20°E., 25.74 ft. mkd. ¼ S (partly visible) and BT (visible), bark scribed.
36" I.Cedar N.56°W., 30.40 ft., no scribing, burned out by ground fire.
Monumented with 1½" x 32" galv. iron pipe.
Scribed -20" W.Fir N.52°30'E., 23.5 ft. mkd. ¼ S S16 T32S R6W RS841 BT.
Tree measurements are current at breast height.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #910 Surveyed, Aug/Sept. 1976 - (DCSO records Vol. 41 Page(s) 16321)

The ¼ sec. cor., perpetuated and recorded by Brandt, 1970, monumented with an iron pipe 1½" dia., firmly set, projecting 3" above ground, from which the remains of the original bearing trees:
A sawed Cedar stump 48" dia., bears N.57°W. 46 lks., no marks visible.
A Cedar 50" dia., bears S.20°E., 39 lks. dist., with illegible scribe marks visible on bark blaze.
and a bearing tree mkd. by Brandt:
A W.Fir 22" dia., bears N.52½°E., 37 lks. dist., with scribe marks ¼ S16 32S R6W RS 841 BT visible on partially healed blaze.
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, directly over iron pipe, with brass cap marked
T 32 S R 6 W
¼ $\frac{S\ 16}{S\ 21}$
1976
from which a new bearing tree
A Cedar 23" dia., bears S.49°E., 42 lks., mkd. ¼ S21 BT.

Cont.

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2125, surveyed July/Nov. 2005 - (DCSO records Vol. 55 Page(s) 21470 & 21467)

The ¼ sec. cor. of secs. 16 and 21, monumented with an iron post, 2½" dia., firmly set, projecting 12" above the ground, with a brass cap mkd. T 32 S R 6 W

1/4 $\frac{S\ 16}{S\ 21}$
1976

from which the remains of the original bearing trees
A cedar snag, 48" dia., bears S.20°E., 25.7 ft., with no marks visible on open blaze.
A sawed cedar stump, 48" dia., bears N.57°W., 30.4 ft., no marks visible.
and the remains of a BT mkd. by Brandt
A sawed fir stump, 22" dia., bears N.52½°E., 24.4 ft. no marks visible.
and a bearing tree mkd. by Roseberry and Aanrud
A cedar, 26" dia., bears S.49°E., 27.7 ft. with a healed blaze.
and a new bearing tree
A fir, 4" dia., bears N.55°E., 26.8 ft., mkd. X at breast height and BT at the base. (MagNail placed left side center at base.)

The geographic position (NAD 1983 (CORS 96)) of the ¼ section corner of sections 16 and 21, as determined by a conventional tie to a temporary point, established utilizing NAVSTAR Global Positioning System (GPS) static data and National Geodetic Survey Online Positioning User Service (OPUS) with continuously operating reference stations "CAPE BLANCO", "DODSON BUTTE", and "YREKA", is as follows:

Latitude: 42° 46' 58.42" N.
Longitude: 123° 25' 00.88" W.