

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 9 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8685-86)

Set a Cedar post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on N. face, from which
A Pine 30" dia., bears N.8°E., 52 lks. dist. mkd. 1/4 S BT
A Fir 28" dia., bears S.5°E., 26 lks. dist., mkd. 1/4 S BT

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13991)

The 1/4 sec. cor., monumented with a wood post, 3 x 3 ins. sq., firmly set, protruding 36" above the ground, from which the original bearing trees:

A sawed Sugar Pine stump 36" dia., bears N.8°E., 52 lks. dist., no marks visible on bottom of opened blaze. (rec. a Pine)

The stump hole of a down Fir 32" dia., bears S.5°E., 26 lks. dist., with illegible scribe marks visible on a bark blaze on the Fir.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 6 W
1/4 S 9
S 16
1966

from which new bearing trees

A Fir 15" dia., bears N.83°W., 49 lks. dist., mkd. 1/4 S9 BT.

A Cedar 14" dia., bears S.61°E., 15 lks. dist., mkd. 1/4 S16 BT.

Reset wood post alongside iron post.

BLM survey by Mark Dixon and Henry Hartley, Cadastral Surveyors, under Group #1337, surveyed July/Sept. 1989 (DCSO records Vol. 48 Page(s) 18566-67)

The 1/4 sec. cor., monumented with an iron post, 2 1/2" dia., firmly set, projecting 5" above ground with 1966 brass cap. from which the remains of the original bearing trees

A sawed Sugar Pine stump 48" dia., bears N.8°E., 52 lks. dist., with a partially exposed face, no marks visible.

A root hole bears S.5°E., 26 lks. dist., with a down Fir 32" dia., alongside, no marks visible.

and bearing trees mkd. by Aanrud

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar 20" dia., bears S.69 3/4°E., 15 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record, S.61°E.)
A Fir 20" dia., bears N.84½°W., 49 lks. dist., with healed blaze. (Record, N.83°W.)

and a bearing tree mkd. by person(s) unknown
A Cedar 24" dia., bears S.36½°W., 20½ lks. dist., with healed blaze and illegible cruiser mark.

Fd. OK by D. Edwards, Oct. 2003 - M143-23