

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8687)

-----  
An Alder tree, 6" dia., which I marked  $\frac{1}{4}$  S. on N. face for  $\frac{1}{4}$  sec. cor., from which

A Hemlock 14" dia., bears N.10°W., 37 lks. dist., mkd.  $\frac{1}{4}$  S BT.

A Dogwood 8" dia., bears S.60°E., 32 lks. dist., mkd.  $\frac{1}{4}$  S BT.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Sept. 1967 - C.S. File 54/31-4

-----  
Found - Orig. 14" now 23" Hemlock, N.10°W., 24.4 ft. faint bark scribe "BT"

No trace of Dogwood or Alder corner tree.

As this corner now falls in edge of creek, I renew as follows:

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 6 W

W.C. 15.0 ft. East to

$\frac{1}{4}$   $\frac{S}{S}$   $\frac{4}{9}$

1967

New BTs -22" Cedar N.29 $\frac{1}{2}$ °E., 8.5 ft. mkd. W.C.  $\frac{1}{4}$  S4 CS BT

11" W.Fir S.6 $\frac{1}{2}$ °W., 7.0 ft. mkd. W.C.  $\frac{1}{4}$  S9 CS BT.

-----  
Fd. OK, by O. Frederick, Feb. 1985, C.S. File 63/11 and M 90-67