

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCS0 records Vol. 20 Page(s) 8650)

Set ¼ sec. post, from which
A B.Oak 18" dia., bears N.13°W., 250 lks. dist.
A W.Oak 14" dia., bears N.5°W., 235 lks. dist.

Ben B. Irving, Surveyor - F. Smith, R. Irving, witnesses - July 11, 1949 - C.S. File 43/134

Set from O.B.T.s
Set ¾" iron rod. Marked new BTs as follows:
24" W.Oak blazed and scribed ¼ S34 CS BT, N.6°31'E., 108.7 ft. - set brass disc.
18" W.Oak blazed and scribed ¼ S33 CS BT, N.69°21'W., 44.0 ft. - set brass disc.

Douglas Co. Surveyors Office - James Byron, Deputy - M. Godfrey, S. Bilow, crew - May 21, 1958 - C.S. File 49/91-1

Found - ¾" Iron rod at fence corner and both BTs as recorded by B.B.I., 1949. Both are now stumps and each has good scribing and check bearing and distance.
New BTs - 13" W.Oak bears N.88½°W., 107.6 ft. scribed ¼ S33 CS BT.
7" W.Oak bears N.83½°E., 52.2 ft scribed ¼ S34 CS BT

Fd. OK, per Max Hull, July 1984, C.S. File 58/299
Fd. OK by R. Wytcherley, July 2001 - M137-18 & CS65/38-3E

Ray Wytcherly - For: Swanson Group Inc. - July 2006 - M151-31

Found - ¾" IR per C.S. 43/134 13" above ground from which:
An Oak BT per C.S. 49/91, 13" dia. in 1958 bears N.88½°W., 107.6 ft.
The NE corner of a railroad tie fence corner bears South 1.0 ft.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 10/24/2006 - C.S. File 67/14-35

Found - ¾" dia., smooth iron rod is loose & bent, projects above ground. 21" 1949
24" W.Oak now rotted & fallen, no marks visible, roothole checks well for bearing & dist. (rec. N.6°31'E., 108.7') 1949 continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

18" W.Oak now 16" dia., burnt rotted stump, 2½ ft. tall, no marks visible, bears N.69½°W., 44.0 ft. (rec. N.69°21'W., 44.0') 1949

13" W.Oak now 17" dia., fully healed double blaze. Has fence wire nailed to north face bears N.88½°W., 107.6' (rec. N.88½°W., 107.6') 1958

No trace of other 1958 BT (Rec. N.83½°E., 52.2')

New - Referenced position of bent I.Rod. Removed & set 1¼"x34" iron pipe w/2½" brass cap (properly mkd) at referenced position. Straightened out ¾" I.Rod & reset on south edge of BC/IP. BC/IP projects 4" above ground.

12" dia., Ponderosa Pine, double blazed & scribed "¼ S34 CS BT" bears S.19½°E., 24.8 ft.

13" dia., Madrone, double blazed & scribed "¼ S33 CS BT" bears N.73°W., 33.0 ft.

Power Pole No. "L-3-24", 12" dia., at angle point in elec. line R/W bars N.18¾°E., 50.7 ft.

Note - Corner lies 1.2 ft. North of fence corner with fences extending East, West, & South.
Compass decl. 16½°E.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21440-1)

The ¼ sec. cor. of secs. 33 and 34, perpetuated from original evidence, no longer in existence, by the Douglas County Surveyor's Office, in 1949, 1958, and 2006, and utilized by various Oregon Professional Surveyors, monumented with an iron post, 1½" dia., firmly set, projecting 4" above the ground, with a 2½" dia. brass cap mkd.

T 32 S
¼
R 6 W
S 33 | S 34
2006

from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1949

A sawed W.Oak stump, 13" dia., bears N.69½°W., 44.8 ft., no marks visible.

and a bearing tree mkd. by the Douglas County Surveyor's Office in 1958

A W.Oak, 17" dia., bears S.89¾°W., 107.6 ft., with a healed upper and lower blazes.

and bearing trees mkd. by the Douglas County Surveyor's Office in 2006

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A ponderosa pine, 12" dia., bears S.19½°E., 24.8 ft., with scribe marks ¼ S34 visible on open upper blaze and CSBT visible on open lower blaze.

A madrone, 12" dia., bears N.73°W., 33.0 ft., with scribe marks ¼ S33 visible on open upper blaze and CSBT visible on open lower blaze.

The corner is located 1 ft. N. of corner of fences extending E, S, and W.