

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8651)

Set ¼ sec. post, from which
A W.Oak 8" dia., bears S.67°W., 66 lks. dist.
A W.Oak 9" dia., bears N.62°E., 125 lks. dist.

Cor. Fd. and used in survey for H.E. Cliff, Nov. 21, 1873, Field Book 97 Page 31

George J. Wenderoth, Deputy Co. Surveyor - Frank Loso, witness - Sept. 1948 (no record source found, information from old Ren. #18, T32-6)

No BTs to be found. 1" I.P. said to be corner by J.K. Howard Mkd - 28" W.Oak S.87°17'W., 58.0 ft.
14" Madrone S.23°15'E., 53.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Sept. 1967 - C.S. File 54/53-4

Found - 1" Iron pipe at ¼ corner.
14" Laurel now 16", S.23°E., 53.0 ft. scribe visible, ¼S CS BT
28" W.Oak, now dead, S.87°W., 58.0 ft. scribe visible, ¼S CS BT
New BT - 6" D.Fir N.69°W., scribed ¼ S28 CS BT.
This corner lies on East slope of small ridge, top of said ridge bears West, 60.0 ft.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #910 Surveyed, Aug./Sept. 1976 - (DCSO records Vol. 41 Page(s) 16311-12)

The ¼ sec.cor. perpetuated by Wenderoth, 1948, from original evidence no longer in existence, monumented with an iron pipe, 1" dia., firmly set, projecting 4" above ground, from which the remains of bearing trees mkd. by Wenderoth:
A Madrone 19" dia., bears S.25½°E., 82 lks. dist., with illegible scribe marks visible on partially healed double blaze.
A root hole, bears S.85°W., 89 lks. dist.
and a bearing tree mkd. by the County in 1967
A Fir 6" dia., bears N.69½°W., 29½ lks. dist., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in
the ground, directly over iron pipe, with brass cap marked
(Cont. Next Page)

T 32 S R 6 W

1/4

S 28 | S 27

1976

Corner is located at intersection of wire fences, fences
extend N., S., E., and W.

Fd. OK, Jan. 1991, M 111-34