

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8651)

-----  
Set post cor. to secs. 21, 22, 27 and 28, from which  
A B.Oak 11" dia., bears S.17°E., 129 lks. dist.  
A Laurel 10" dia., bears N.52°E., 93 lks. dist.  
A B.Oak 10" dia., bears N.61°W., 121 lks. dist.  
A B.Oak 12" dia., bears S.39°W., 102 lks. dist.

Fd. and used by Byars in GLO 1881 survey (DCSO records, Vol. 20 Pgs 8676-77)

Not Fd. by John Powell, DCSO 10/1967 (added 3/28/2017) C.S. File 54/53-21 - area cut off.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #910 Surveyed, Aug/Sept. 1976 - (DCSO records Vol. 41 Page(s) 16312-13)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 6 W  
S 21 | S 22  
S 28 | S 27  
1976

from which

A Fir 9" dia., bears N.58½°E., 36 lks. dist., mkd. T32S R6W S22 BT.

A Fir 6" dia., bears S.37°E., 56 lks. dist., mkd. T32S R6W S27 BT.

A Fir 7" dia., bears S.64½°W., 43 lks. dist., mkd. T32S R6W S28 BT.

A Fir 9" dia., bears N.51½°W., 42 lks. dist., mkd. T32S R6W S21 BT.

From this point, a locally established corner of which I have no record, bears N.78½°W., 0.395 chs. dist., monumented with an iron pipe, 1½" dia., firmly set, projecting 18" above ground.

Fd. OK, Jan. 1991, M 111-34