TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8678-79)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S. on W. face, from which
A Fir 48" dia., bears S.72°W., 13 lks. dist., mkd. ¼ S BT.
A Fir 48" dia., bears S.45°E., 19 lks. dist., mkd. ¼ S BT.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13990)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 32 S R 6 W
¼
S 16 S 15
1966
from which
A Fir 5" dia., bears N.60°E., 19 lks. dist., mkd. X BT.
A Cedar 18" dia., bears S.37°W., 22 lks. dist., mkd. ¼ S 16 BT.

Cor. Fd. and used in BLM resurvey by Dixon and Hartley, under Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48 Pages 18575-76)