

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8679)

-
- Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs., 9, 10, 15 and 16, and marked T32S R6W S10 on NE.; S15 on SE.; S16 on SW.; and S9 on NW. faces, with 4 notches on S. and 3 notches on E. edges, from which
- A Cedar 14" dia., bears N.20°E., 9 lks. dist., mkd. T32S R6W S10 BT.
 - A Chinquapin 10" dia., bears S.72°E., 32 lks. dist., mkd. T32S R6W S15 BT.
 - A Fir 8" dia., bears S.46°W., 16 lks. dist., mkd. T32S R6W S16 BT.
 - A Fir 20" dia., bears N.42°W., 22 lks. dist., mkd. T32S R6W S9 BT.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13990-91)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 32	S R 6 W
<u>S 9</u>	<u>S 10</u>
S16	S 15
1966	

- from which
- A Fir 18" dia., bears N.15°E., 47 lks. dist., mkd. T32S R6W S10 BT.
 - A Yellow Pine 5" dia., bears S.54°E., 18 lks. dist., mkd. X BT.
 - A Chinquapin 8" dia., bears S.46°W., 31 lks. dist., mkd. T32S R6W S16 BT.
 - A Fir 15" dia., bears N.33°W., 43 lks. dist., mkd. T32S R6W S9 BT.

BLM survey by Mark Dixon and Henry Hartley, Cadastral Surveyors, under Group #1337, surveyed July/Sept. 1989 (DCSO records Vol. 48 Page(s) 18566)

The sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with 1966 brass cap., from which bearing trees mkd. by Aanrud

- A Fir 21" dia., bears N.15°E., 47 lks. dist. with healed blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Secs. cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Yellow Pine 13" dia., bears S.54°E., 18 lks. dist., with healed blaze.

A Chinkapin snag 7" dia., bears S.46°W., 31 lks. dist., with scribe marks T32S R6W S16 BT visible on partially healed blaze.

A Fir 17" dia., bears N.33°W., 43 lks. dist., with healed blaze.

No suitable trees available in sec. 16.

From this point, a point established by person(s) unknown, bears N.74°40'30"E., 0.875 chs. dist., monumented with an iron pipe 1" dia., firmly set, projecting 21" above ground.

Fd. OK by D. Edwards, Oct. 2003 - M143-23